



# ANCHOR SELECTOR / Chemical — Rods & Elements



For Use with		Material	Available thread sizes (● = off the shelf ○ = make to order, up to 144" in length)																SafeSet Installation
Injectable adhesives	Adhesive capsules	Steel grade / coating	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	7/8"	1"	1-1/8"	1-1/4"	1-1/2"	1-3/4"	2"	2-1/4"	2-1/2"		

## Cone Shaped "Zero-Cleaning" Anchor Rods

<b>HIT-Z</b>		■ with HIT-HY 200				●	●	●	●										no bore hole cleaning required
<b>HIT-Z-R</b>		■ with HIT-HY 200				●	●	●	●										(above 5°C / 41°F, with HIT-HY 200)

## All-Threaded Anchor Rods

<b>HAS-V-36</b>		■		Carbon steel, zinc plated	ASTM F1554 Grade 36	●	●	●	●	●	●	●	○	○	○	○	○		Installation with SafeSet technology, using suitable TE-CD or TE-YD hollow drill bits and Hilti vacuum cleaner	
<b>HAS-E-55</b>		■	■		ASTM F1554 Grade 55				●	●	●	●	●	○	●	○	○	○		
<b>HAS-B-105</b>		■	■		ASTM F1554 Grade 105				●	●	●	●	●	○	●	○	○	○		○
<b>HAS-V-36 HDG</b>		■		Carbon steel, hot dip galvanized	ASTM F1554 Grade 36				●	●	●	●	●	○	○	○	○			
<b>HAS-E-55 HDG</b>		■	■		ASTM F1554 Grade 55				○	○	○	○	○	○	○	○	○	○		
<b>HAS-B-105 HDG</b>		■	■		ASTM F1554 Grade 105				●	●	●	●	●	○	●	○	○	○		○
<b>HAS-R 304 SS</b>		■	■	Stainless steel	Stainless steel 304	○			●	●	●	●	●	○	○	○	○			
<b>HAS-R 316 SS</b>		■	■		Stainless steel 316		○			●	●	●	●	○	○	○	○	○		

## Internally Threaded Inserts

<b>HIS-N</b>		■	■	Carbon steel, zinc plated					●	●	●	●							Installation with SafeSet technology, using suitable TE-CD or TE-YD hollow drill bits and Hilti vacuum cleaner
<b>HIS-RN</b>		■	■	Stainless steel 316					●	●	●	●							
<b>HIT-IC</b>		■ with HIT-HY 270		Carbon steel, zinc plated						●	●	●							

