

<p>NOTE: FOR 1 HOUR ASSEMBLY, ONE LAYER OF 5/8 IN THICK GYPSUM BOARD IS REQUIRED.</p>		<table><tr><td>HW-D-0758</td><td>TOP OF WALL JOINT: GYPSUM CHASE WALL ASSEMBLY</td></tr><tr><td>ASSEMBLY RATING: 2HR</td><td></td></tr></table>		HW-D-0758	TOP OF WALL JOINT: GYPSUM CHASE WALL ASSEMBLY	ASSEMBLY RATING: 2HR	
HW-D-0758	TOP OF WALL JOINT: GYPSUM CHASE WALL ASSEMBLY						
ASSEMBLY RATING: 2HR							
<p>NOTE: FOR 1 HOUR ASSEMBLY, ONE LAYER OF 5/8 IN THICK GYPSUM BOARD IS REQUIRED.</p>		<table><tr><td>HW-D-0757</td><td>TOP OF WALL JOINT: GYPSUM WALL ASSEMBLY</td></tr><tr><td>ASSEMBLY RATING: 2HR</td><td></td></tr></table>		HW-D-0757	TOP OF WALL JOINT: GYPSUM WALL ASSEMBLY	ASSEMBLY RATING: 2HR	
HW-D-0757	TOP OF WALL JOINT: GYPSUM WALL ASSEMBLY						
ASSEMBLY RATING: 2HR							
<p>NOTE: FOR 1 HOUR ASSEMBLY, ONE LAYER OF 5/8 IN THICK GYPSUM BOARD IS REQUIRED.</p>		<table><tr><td>HW-D-0268</td><td>TOP OF WALL JOINT: CONCRETE WALL OR BLOCK WALL ASSEMBLY</td></tr><tr><td>ASSEMBLY RATING: 2HR</td><td></td></tr></table>		HW-D-0268	TOP OF WALL JOINT: CONCRETE WALL OR BLOCK WALL ASSEMBLY	ASSEMBLY RATING: 2HR	
HW-D-0268	TOP OF WALL JOINT: CONCRETE WALL OR BLOCK WALL ASSEMBLY						
ASSEMBLY RATING: 2HR							
<p>NOTE: FOR 1 HOUR ASSEMBLY, ONE LAYER OF 5/8 IN THICK GYPSUM BOARD IS REQUIRED.</p>		<table><tr><td>HW-D-0403</td><td>TOP OF WALL JOINT: CONCRETE WALL OR BLOCK WALL ASSEMBLY</td></tr><tr><td>ASSEMBLY RATING: 2HR</td><td></td></tr></table>		HW-D-0403	TOP OF WALL JOINT: CONCRETE WALL OR BLOCK WALL ASSEMBLY	ASSEMBLY RATING: 2HR	
HW-D-0403	TOP OF WALL JOINT: CONCRETE WALL OR BLOCK WALL ASSEMBLY						
ASSEMBLY RATING: 2HR							
<p>NOTE: FOR 1 HOUR ASSEMBLY, ONE LAYER OF 5/8 IN THICK GYPSUM BOARD IS REQUIRED.</p>		<table><tr><td>HW-D-0209</td><td>TOP OF WALL JOINT: GYPSUM WALL ASSEMBLY</td></tr><tr><td>ASSEMBLY RATING: 2HR</td><td></td></tr></table>		HW-D-0209	TOP OF WALL JOINT: GYPSUM WALL ASSEMBLY	ASSEMBLY RATING: 2HR	
HW-D-0209	TOP OF WALL JOINT: GYPSUM WALL ASSEMBLY						
ASSEMBLY RATING: 2HR							
<p>NOTE: FOR 1 HOUR ASSEMBLY, ONE LAYER OF 5/8 IN THICK GYPSUM BOARD IS REQUIRED.</p>		<table><tr><td>HW-D-0824</td><td>TOP OF WALL JOINT: GYPSUM SHAFT WALL ASSEMBLY</td></tr><tr><td>ASSEMBLY RATING: 2HR</td><td></td></tr></table>		HW-D-0824	TOP OF WALL JOINT: GYPSUM SHAFT WALL ASSEMBLY	ASSEMBLY RATING: 2HR	
HW-D-0824	TOP OF WALL JOINT: GYPSUM SHAFT WALL ASSEMBLY						
ASSEMBLY RATING: 2HR							
<p>NOTE: FOR 1 HOUR ASSEMBLY, ONE LAYER OF 5/8 IN THICK GYPSUM BOARD IS REQUIRED.</p>		<table><tr><td>BW-S-0002</td><td>BOTTOM OF WALL JOINT: GYPSUM WALL ASSEMBLY</td></tr><tr><td>ASSEMBLY RATING: 2HR</td><td></td></tr></table>		BW-S-0002	BOTTOM OF WALL JOINT: GYPSUM WALL ASSEMBLY	ASSEMBLY RATING: 2HR	
BW-S-0002	BOTTOM OF WALL JOINT: GYPSUM WALL ASSEMBLY						
ASSEMBLY RATING: 2HR							
<p>NOTE: FOR 1 HOUR ASSEMBLY, ONE LAYER OF 5/8 IN THICK GYPSUM BOARD IS REQUIRED.</p>		<table><tr><td>WW-S-0074</td><td>WALL TO WALL JOINT: GYPSUM WALL ASSEMBLY</td></tr><tr><td>ASSEMBLY RATING: 2HR</td><td></td></tr></table>		WW-S-0074	WALL TO WALL JOINT: GYPSUM WALL ASSEMBLY	ASSEMBLY RATING: 2HR	
WW-S-0074	WALL TO WALL JOINT: GYPSUM WALL ASSEMBLY						
ASSEMBLY RATING: 2HR							
<p>NOTE: FOR 1 HOUR ASSEMBLY, ONE LAYER OF 5/8 IN THICK GYPSUM BOARD IS REQUIRED.</p>		<table><tr><td>HW-D-0209</td><td>BOTTOM OF WALL JOINT: GYPSUM WALL ASSEMBLY</td></tr><tr><td>ASSEMBLY RATING: NON-FIRE RATED</td><td></td></tr></table>		HW-D-0209	BOTTOM OF WALL JOINT: GYPSUM WALL ASSEMBLY	ASSEMBLY RATING: NON-FIRE RATED	
HW-D-0209	BOTTOM OF WALL JOINT: GYPSUM WALL ASSEMBLY						
ASSEMBLY RATING: NON-FIRE RATED							
<p>NOTE: FOR 1 HOUR ASSEMBLY, ONE LAYER OF 5/8 IN THICK GYPSUM BOARD IS REQUIRED.</p>		<table><tr><td>HW-D-0824</td><td>TOP OF WALL JOINT: CONCRETE WALL OR BLOCK WALL ASSEMBLY</td></tr><tr><td>ASSEMBLY RATING: NON-FIRE RATED</td><td></td></tr></table>		HW-D-0824	TOP OF WALL JOINT: CONCRETE WALL OR BLOCK WALL ASSEMBLY	ASSEMBLY RATING: NON-FIRE RATED	
HW-D-0824	TOP OF WALL JOINT: CONCRETE WALL OR BLOCK WALL ASSEMBLY						
ASSEMBLY RATING: NON-FIRE RATED							
<p>NOTE: FOR 1 HOUR ASSEMBLY, ONE LAYER OF 5/8 IN THICK GYPSUM BOARD IS REQUIRED.</p>		<table><tr><td>HW-D-0268</td><td>TOP OF WALL JOINT: CONCRETE WALL OR BLOCK WALL ASSEMBLY</td></tr><tr><td>ASSEMBLY RATING: NON-FIRE RATED</td><td></td></tr></table>		HW-D-0268	TOP OF WALL JOINT: CONCRETE WALL OR BLOCK WALL ASSEMBLY	ASSEMBLY RATING: NON-FIRE RATED	
HW-D-0268	TOP OF WALL JOINT: CONCRETE WALL OR BLOCK WALL ASSEMBLY						
ASSEMBLY RATING: NON-FIRE RATED							
<p>NOTE: FOR 1 HOUR ASSEMBLY, ONE LAYER OF 5/8 IN THICK GYPSUM BOARD IS REQUIRED.</p>		<table><tr><td>HW-D-0403</td><td>TOP OF WALL JOINT: GYPSUM WALL ASSEMBLY</td></tr><tr><td>ASSEMBLY RATING: NON-FIRE RATED</td><td></td></tr></table>		HW-D-0403	TOP OF WALL JOINT: GYPSUM WALL ASSEMBLY	ASSEMBLY RATING: NON-FIRE RATED	
HW-D-0403	TOP OF WALL JOINT: GYPSUM WALL ASSEMBLY						
ASSEMBLY RATING: NON-FIRE RATED							

- General Notes:
1. Refer to section 07840 of the specifications. For Quality Control requirements, refer to the Quality Control portion of the specification.
  2. Details shown are typical details. If field conditions do not match requirements of typical details, approved alternate details shall be utilized. Field conditions and dimensions need to be verified for compliance with the details, including but not limited to the following:
    - \* Minimum and maximum Width of Joints
    - \* Type and thickness of fire-rated construction. The minimum assembly rating of the firestop assembly shall meet or exceed the highest rating of the adjacent construction.
  3. If alternate details matching the field conditions are not available, Manufacturer's engineering judgment drawings are acceptable. Drawings shall follow the International Firestop Council (IFC) Guidelines for Evaluating Firestop Systems Engineering Judgments.
  4. References:
    - \* Underwriter's Laboratories Fire Resistance Directory
    - \* Intertek Directory of Listed Products
    - \* NFPA 101 Life Safety Code
    - \* All governing local and regional building codes
  5. Firestop System installation must meet requirements of cUL 2079 tested assemblies that provide the required assembly rating.
  6. All rated assemblies shall be prominently labeled with the following information:
    - \* ATTENTION: Fire Rated Assembly
    - \* cUL System #
    - \* Product(s) used
    - \* Hourly Rating (Assembly Rating)
    - \* Installation Date

<Notes to designer (delete this note after reading and replace with title block information)>  
1. Any modification to these details cULd rescULt in an application/system not meeting the cUL or Intertek Classification or the intended temperature or fire ratings.  
2. Details shown are up to date as of February 2019.  
3. For additional information on the details, refer to the most current "Underwriter's Laboratories Fire Resistance Directory (volume 2.)"