

HIT-HY 200-R

Safety information for 2-Component-products

Issue date: 20/12/2021

Revision date: 20/12/2021

Supersedes: 25/09/2018

Version: 3.7

SECTION 1: Kit identification

1.1 Product identifier

Product name

HIT-HY 200-R



Product code

BU Anchor

1.2 Details of the supplier of the Safety information for 2-Component-products

Hilti Entwicklungsgesellschaft mbH

Hiltistraße 6

86916 Kaufering - Deutschland

T +49 8191 906876

anchor.hse@hilti.com

SECTION 2: General information

Storage

Storage temperature : 5 - 25 °C

A SDS for each of these components is included. Please do not separate any component SDS from this cover page

This Kit should be handled in accordance with good laboratory practices and appropriate personal protective equipment should be used

SECTION 3: Kit contents

Classification of the Product

Classification (GHS CA)

Serious eye damage/eye irritation, Category 2 H319
Skin sensitisation, Category 1 H317

Label elements

GHS CA labelling

Hazard pictograms (GHS CA)



GHS07

Signal word (GHS CA)

Warning

Hazardous ingredients

methacrylates, dibenzoyl peroxide

Hazard statements (GHS CA)

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

Precautionary statements (GHS CA)

P280 - Wear eye protection, protective clothing, protective gloves.

P262 - Do not get in eyes, on skin, or on clothing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P302+P352 - IF ON SKIN: Wash with plenty of water.

HIT-HY 200-R


Safety information for 2-Component-products

Additional information

2-Component-foilpack, contains:

Component A: Urethane methacrylate resin, inorganic filler

Component B: Dibenzoyl peroxide, phlegmatized



Name	General description	Quantity	Unit	Classification (GHS CA)
HIT-HY 200-R, A		1	pcs (pieces)	Skin Sens. 1, H317
HIT-HY 200-R, B		1	pcs (pieces)	Eye Irrit. 2, H319 Skin Sens. 1, H317

SECTION 4: General advice

General advice

For professional users only

SECTION 5: Safe handling advice

General measures

Spilled material may present a slipping hazard

Environmental precautions

Prevent entry to sewers and public waters

Notify authorities if liquid enters sewers or public waters

Storage conditions

Keep cool. Protect from sunlight.

Precautions for safe handling

Wear personal protective equipment

Avoid contact with skin and eyes

Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work

Provide good ventilation in process area to prevent formation of vapour

Methods for cleaning up

This material and its container must be disposed of in a safe way, and as per local legislation

Mechanically recover the product

Store away from other materials.

For containment

Collect spillage.

Incompatible materials

Sources of ignition

Direct sunlight

Incompatible products

Strong bases

Strong acids

SECTION 6: First aid measures

First-aid measures after eye contact

Rinse immediately with plenty of water

Remove contact lenses, if present and easy to do. Continue rinsing.

Obtain medical attention if pain, blinking or redness persists

First-aid measures after ingestion

Rinse mouth

Get medical advice/attention.

Do not induce vomiting

Obtain emergency medical attention

First-aid measures after inhalation

Remove person to fresh air and keep comfortable for breathing.

Allow affected person to breathe fresh air

Allow the victim to rest

First-aid measures after skin contact

Wash contaminated clothing before reuse.

Wash with plenty of water/...

If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures general

Take off immediately all contaminated clothing.

Never give anything by mouth to an unconscious person

HIT-HY 200-R

Safety information for 2-Component-products

If you feel unwell, seek medical advice (show the label where possible)

Symptoms/effects after eye contact

May cause severe irritation

May cause an allergic skin reaction.

SECTION 7: Fire fighting measures

Firefighting instructions

Use water spray or fog for cooling exposed containers

Exercise caution when fighting any chemical fire.

Prevent fire fighting water from entering the environment

Protection during firefighting

Self-contained breathing apparatus

Do not enter fire area without proper protective equipment, including respiratory protection

Hazardous decomposition products in case of fire

Thermal decomposition generates :

Thermal decom
Carbon dioxide

Carbon monoxide

SECTION 8: Other information

No data available

HIT-HY 200-R, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Issue date: 12/20/2021

Revision date: 12/20/2021

Supersedes: 09/25/2018

Version: 3.7

SECTION 1: Identification

1.1. Product identifier

Product form	Mixture
Product name	HIT-HY 200-R, B
Product code	BU Anchor

1.2. Recommended use and restrictions on use

Recommended use	Composite mortar component for fasteners in the construction industry
Restrictions on use	For professional use only

1.3. Supplier

Supplier
Hilti (Canada) Corp.
2360 Meadowpine Boulevard
L5N 6S2 Mississauga, Ontario - Canada
T +1905 8139200
1-800-363-4458 toll free - F +1 905 813 9009

Department issuing data specification sheet
Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
86916 Kaufering - Deutschland
T +49 8191 906876
anchor.hse@hilti.com

1.4. Emergency telephone number

Emergency number	Chem-Trec Tel.: 1 800 424 9300 (USA, PR, Virgin Islands, Canada) Tel.: 703 527 3887 (Other countries)
------------------	---

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Serious eye damage/eye irritation, Category 2A	H319	Causes serious eye irritation.
Skin sensitisation, Category 1	H317	May cause an allergic skin reaction.
Full text of H-statements: see section 16		

2.2. GHS Label elements, including precautionary statements

GHS CA labelling

Hazard pictograms (GHS CA)



Signal word (GHS CA)

Warning

Hazard statements (GHS CA)

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

Precautionary statements (GHS CA)

P280 - Wear eye protection, protective clothing, protective gloves.

P262 - Do not get in eyes, on skin, or on clothing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P302+P352 - IF ON SKIN: Wash with plenty of water.

2.3. Other hazards

No additional information available

HIT-HY 200-R, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

2.4. Unknown acute toxicity (GHS CA)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Quartz (SiO ₂)	quartz / quartz (SiO ₂) / quartz flour, 1%≤conc respirable crystalline silica<10% / silicon (di)oxide (quartz), 1%≤conc respirable crystalline silica<10%	(CAS-No.) 14808-60-7	40 – 60	Carc. 1A, H350
dibenzoyl peroxide	dibenzoyl peroxide; benzoyl peroxide	(CAS-No.) 94-36-0	10 – 25	Org. Perox. B, H241 Eye Irrit. 2A, H319 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	Wash contaminated clothing before reuse. Wash with plenty of water/.... If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	Rinse mouth. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.
First-aid measures general	Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact	May cause an allergic skin reaction.
Symptoms/effects after eye contact	May cause severe irritation.
Potential adverse human health effects and symptoms	No additional information available.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media Water spray. Carbon dioxide. Dry powder. Foam. Sand.

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media Do not use a heavy water stream.

HIT-HY 200-R, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

5.3. Specific hazards arising from the hazardous product

Hazardous decomposition products in case of fire Thermal decomposition generates : Carbon dioxide. Carbon monoxide.

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures Spilled material may present a slipping hazard.

6.2. Methods and materials for containment and cleaning up

For containment	Collect spillage.
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. Store away from other materials.
Other information	Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.
Hygiene measures	Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Keep cool. Protect from sunlight.
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.
Heat and ignition sources	Keep away from heat and direct sunlight.
Storage temperature	5 – 25 °C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional information The product has a pasty consistency. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Appropriate engineering controls

Appropriate engineering controls	Ensure adequate ventilation.
Environmental exposure controls	Avoid release to the environment.

HIT-HY 200-R, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Safety glasses. Gloves. Protective clothing. Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

Type	Material	Permeation	Thickness (mm)	Penetration
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0,12	

Eye protection:

Wear security glasses which protect from splashes

Type	Field of application	Characteristics
Safety glasses	Droplet	clear

Skin and body protection:

Wear suitable protective clothing

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	white
Odour	characteristic
Odour threshold	Not determined
pH	No data available
Relative evaporation rate (butylacetate=1)	No data available
Relative evaporation rate (ether=1)	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	No data available
Flash point	No data available
Auto-ignition temperature	Not self-igniting
Decomposition temperature	No data available
Flammability (solid, gas)	Non flammable.
Vapour pressure	No data available
Vapour pressure at 50 °C	No data available
Relative density	No data available
Density	1.9 g/ml AW 4.3.23
Solubility	Water: Not miscible

HIT-HY 200-R, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Partition coefficient n-octanol/water (Log Pow)	No data available
Viscosity, kinematic	21052.632 mm ² /s
Viscosity, dynamic	40 Pa·s HN-0333
Explosive properties	Product is not explosive.
Explosive limits	No data available

9.2. Other information

SADT : 65 °C

SECTION 10: Stability and reactivity

Reactivity	No additional information available
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	No additional information available.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures.
Incompatible materials	Strong acids. Strong bases.
Hazardous decomposition products	fume. Carbon monoxide. Carbon dioxide. Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified
Skin corrosion/irritation	Not classified
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory or skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified

HIT-HY 200-R, B

Viscosity, kinematic	21052.632 mm ² /s
Potential adverse human health effects and symptoms	No additional information available.
Symptoms/effects after skin contact	May cause an allergic skin reaction.
Symptoms/effects after eye contact	May cause severe irritation.

HIT-HY 200-R, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	Not classified
Hazardous to the aquatic environment, long-term (chronic)	Not classified

dibenzoyl peroxide (94-36-0)	
LC50 - Fish [2]	0.0602 mg/l (96h; Oncorhynchus mykiss; ECHA)
EC50 - Crustacea [1]	0.11 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 algae	0.0711 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
NOEC chronic fish	0.001 mg/l
Partition coefficient n-octanol/water (Log Pow)	3.71
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
NOEC (acute)	0.0316 mg/l (96h; Oncorhynchus mykiss; ECHA)

12.2. Persistence and degradability

HIT-HY 200-R, B	
Persistence and degradability	Not established.
Quartz (SiO₂) (14808-60-7)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
dibenzoyl peroxide (94-36-0)	
Persistence and degradability	Readily biodegradable in water. Not established. May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

HIT-HY 200-R, B	
Bioaccumulative potential	Not established.
Quartz (SiO₂) (14808-60-7)	
Bioaccumulative potential	No bioaccumulation data available.
dibenzoyl peroxide (94-36-0)	
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).
Partition coefficient n-octanol/water (Log Pow)	3.71
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)

12.4. Mobility in soil

Quartz (SiO₂) (14808-60-7)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for mobility in soil.
dibenzoyl peroxide (94-36-0)	
Surface tension	No data available (test not performed)
Ecology - soil	Low potential for mobility in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
Partition coefficient n-octanol/water (Log Pow)	3.71

HIT-HY 200-R, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

12.5. Other adverse effects

Ozone	Not classified
Other information	Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste)	Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID
14.1. UN number			
UN 3077	UN 3077	UN 3077	UN 3077
14.2. UN proper shipping name			
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide)	Environmentally hazardous substance, solid, n.o.s. (dibenzoyl peroxide)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide)
Transport document description	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide), 9, III, (-)	UN 3077 Environmentally hazardous substance, solid, n.o.s. (dibenzoyl peroxide), 9, III, MARINE POLLUTANT	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide), 9, III
14.3. Transport hazard class(es)			
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
not restricted according ADR Special Provision SP375, IATA-DGR Special Provision A197 and IMDG-Code 2.10.2.7			

HIT-HY 200-R, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

14.6. Special precautions for user

Overland transport

Classification code (ADR)	M7
Special provisions (ADR)	274, 335, 375, 601
Limited quantities (ADR)	5kg
Packing instructions (ADR)	P002, IBC08, LP02, R001
Mixed packing provisions (ADR)	MP10
Transport category (ADR)	3
Orange plates	

Tunnel restriction code (ADR)

Transport by sea

Special provisions (IMDG)	274, 335, 966, 967, 969
Limited quantities (IMDG)	5 kg
Packing instructions (IMDG)	LP02, P002
EmS-No. (Fire)	F-A
EmS-No. (Spillage)	S-F
Stowage category (IMDG)	A
Stowage and handling (IMDG)	SW23

Air transport

PCA packing instructions (IATA)	956
PCA max net quantity (IATA)	400kg
CAO packing instructions (IATA)	956
Special provisions (IATA)	A97, A158, A179, A197, A215

Rail transport

Special provisions (RID)	274, 335, 375, 601
Limited quantities (RID)	5kg
Packing instructions (RID)	P002, IBC08, LP02, R001

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

Quartz (SiO₂) (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List)

dibenzoyl peroxide (94-36-0)

Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

Quartz (SiO₂) (14808-60-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

dibenzoyl peroxide (94-36-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

HIT-HY 200-R, B

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 16: Other information

SDS Major/Minor	None
Issue date	12-20-2021
Revision date	12-20-2021
Supersedes	09-25-2018

Indication of changes:

Section	Changed item	Change	Comments
14	Transport information	Modified	

Other information None.

Full text of H-statements:

H241	Heating may cause a fire or explosion.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H350	May cause cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
TLM	Median Tolerance Limit
vPvB	Very Persistent and Very Bioaccumulative

SDS_CA_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

HIT-HY 200-R, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Issue date: 12/20/2021

Revision date: 12/20/2021

Supersedes: 09/25/2018

Version: 3.7

SECTION 1: Identification

1.1. Product identifier

Product form	Mixture
Product name	HIT-HY 200-R, A
Product code	BU Anchor

1.2. Recommended use and restrictions on use

Recommended use	Composite mortar component for fasteners in the construction industry
Restrictions on use	For professional use only

1.3. Supplier

Supplier
Hilti (Canada) Corp.
2360 Meadowpine Boulevard
L5N 6S2 Mississauga, Ontario - Canada
T +1905 8139200
1-800-363-4458 toll free - F +1 905 813 9009

Department issuing data specification sheet
Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
86916 Kaufering - Deutschland
T +49 8191 906876
anchor.hse@hilti.com

1.4. Emergency telephone number

Emergency number	Chem-Trec Tel.: 1 800 424 9300 (USA, PR, Virgin Islands, Canada) Tel.: 703 527 3887 (Other countries)
------------------	---

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Skin sensitisation, Category 1	H317	May cause an allergic skin reaction.
Full text of H-statements: see section 16		

2.2. GHS Label elements, including precautionary statements

GHS CA labelling

Hazard pictograms (GHS CA)



Warning

Signal word (GHS CA)

Hazard statements (GHS CA)

H317 - May cause an allergic skin reaction.

Precautionary statements (GHS CA)

P280 - Wear eye protection, protective clothing, protective gloves.

P262 - Do not get in eyes, on skin, or on clothing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P302+P352 - IF ON SKIN: Wash with plenty of water.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS CA)

No data available

HIT-HY 200-R, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Quartz (SiO ₂)	quartz / quartz (SiO ₂) / quartz flour, 1%≤conc respirable crystalline silica<10% / silicon (di)oxide (quartz), 1%≤conc respirable crystalline silica<10%	(CAS-No.) 14808-60-7	40 – 60	Carc. 1A, H350
2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester		(CAS-No.) 2082-81-7	10 – 25	Skin Sens. 1B, H317
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol	1,2-propanediol, 2-methyl, monomethacrylate / 2-propenoic acid, 2-methyl-, 2-hydroxymethylethyl ester / 2-propenoic acid, 2-methyl-, monoester with 1,2-propanediol / hydroxypropyl methacrylate / methacrylic acid, ester with 1,2-propanediol / methacrylic acid, monoester with 1,2-propanediol / methacrylic acid, monoester with propane-1,2-diol / propylene glycol monomethacrylate / ROCRYL 410	(CAS-No.) 27813-02-1	5 – 10	Eye Irrit. 2A, H319 Skin Sens. 1, H317
1,1'-(p-tolylimino)dipropan-2-ol	DiPpT	(CAS-No.) 38668-48-3	0.1 – 1	Acute Tox. 2 (Oral), H300 Eye Irrit. 2A, H319 Aquatic Chronic 3, H412
2,2'-(m-tolylimino)diethanol		(CAS-No.) 91-99-6	0.1 – 1	Acute Tox. 3 (Oral), H301 Acute Tox. 4 (Dermal), H312 Eye Irrit. 2A, H319

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation

Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures general

Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact

May cause an allergic skin reaction.

Symptoms/effects after eye contact

May cause severe irritation.

Potential adverse human health effects and symptoms

No additional information available.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media Water spray. Carbon dioxide. Dry powder. Foam. Sand.

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media Do not use a heavy water stream.

HIT-HY 200-R, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

5.3. Specific hazards arising from the hazardous product

Hazardous decomposition products in case of fire Thermal decomposition generates : Carbon dioxide. Carbon monoxide.

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures Spilled material may present a slipping hazard.

6.2. Methods and materials for containment and cleaning up

No additional information available

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

No additional information available

7.2. Conditions for safe storage, including any incompatibilities

Incompatible products Strong bases. Strong acids.
Incompatible materials Sources of ignition. Direct sunlight.
Heat and ignition sources Keep away from heat and direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional information The product has a pasty consistency. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Appropriate engineering controls

Appropriate engineering controls Ensure adequate ventilation.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Safety glasses. Gloves. Protective clothing. Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

Type	Material	Permeation	Thickness (mm)	Penetration
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0,12	

Eye protection:

Wear security glasses which protect from splashes

HIT-HY 200-R, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Type	Field of application	Characteristics
Safety glasses	Droplet	clear

Skin and body protection:

Wear suitable protective clothing

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	Light grey
Odour	characteristic
Odour threshold	Not determined
pH	No data available
Relative evaporation rate (butylacetate=1)	No data available
Relative evaporation rate (ether=1)	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	No data available
Flash point	> 109 °C DIN EN ISO 1523
Auto-ignition temperature	Not self-igniting
Decomposition temperature	No data available
Flammability (solid, gas)	Non flammable.
Vapour pressure	No data available
Vapour pressure at 50 °C	No data available
Relative density	No data available
Density	1.8 g/ml AW 4.3.23
Solubility	Water: Not miscible
Partition coefficient n-octanol/water (Log Pow)	No data available
Viscosity, kinematic	27777.778 mm ² /s
Viscosity, dynamic	50 Pa·s HN-0333
Explosive properties	Product is not explosive.
Explosive limits	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

Reactivity	No additional information available
Chemical stability	No additional information available
Possibility of hazardous reactions	No additional information available
Conditions to avoid	No additional information available

HIT-HY 200-R, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Incompatible materials	Strong acids. Strong bases.
Hazardous decomposition products	No additional information available
Hardening time:	No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)

LD50 oral rat	25 mg/kg
LD50 dermal rat	> 2000 mg/kg
ATE CA (oral)	25 mg/kg bodyweight

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)

LD50 oral rat	10066 mg/kg
LD50 dermal rat	> 3000 mg/kg
ATE CA (oral)	10066 mg/kg bodyweight

2,2'-(m-tolylimino)diethanol (91-99-6)

LD50 oral rat	300 – 2000 mg/kg
LD50 dermal rat	> 2000 mg/kg
ATE CA (oral)	300 mg/kg bodyweight
ATE CA (Dermal)	1100 mg/kg bodyweight

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)

LD50 oral rat	> 5000 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; >=2000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	≥ 5000 mg/kg bodyweight (Rabbit; Experimental value)

Skin corrosion/irritation	Not classified
Serious eye damage/irritation	Not classified
Respiratory or skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified

Reproductive toxicity	Not classified
-----------------------	----------------

STOT-single exposure	Not classified
STOT-repeated exposure	Not classified

Aspiration hazard	Not classified
-------------------	----------------

HIT-HY 200-R, A

Viscosity, kinematic	27777.778 mm ² /s
----------------------	------------------------------

Potential adverse human health effects and symptoms	No additional information available.
---	--------------------------------------

Symptoms/effects after skin contact	May cause an allergic skin reaction.
-------------------------------------	--------------------------------------

Symptoms/effects after eye contact	May cause severe irritation.
------------------------------------	------------------------------

HIT-HY 200-R, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) Not classified

Hazardous to the aquatic environment, long-term (chronic) Not classified

1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)

LC50 - Fish [1]	≈ 17 mg/l
LC50 - Other aquatic organisms [1]	245 mg/l
EC50 - Crustacea [1]	28.8 mg/l
Partition coefficient n-octanol/water (Log Kow)	2.1
NOEC (acute)	57.8 mg/l

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)

LC50 - Other aquatic organisms [1]	9.79 mg/l
NOEC (chronic)	20 mg/l
Partition coefficient n-octanol/water (Log Pow)	3.1
NOEC (acute)	7.51 mg/l

2,2'-(m-tolylimino)diethanol (91-99-6)

Partition coefficient n-octanol/water (Log Pow)	1.9
---	-----

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)

LC50 - Fish [1]	493 mg/l (48 h; Leuciscus idus; GLP)
EC50 - Crustacea [1]	> 143 mg/l (48 h; Daphnia magna; GLP)
ErC50 algae	97.2 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
BCF - Fish [1]	≤ 100
BCF - Fish [2]	3.2 Quantitative structure-activity relationship (QSAR)
Partition coefficient n-octanol/water (Log Pow)	0.97 (OECD 102 method)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.9 (log Koc, Calculated value)
Threshold limit - Algae [1]	> 97.2 mg/l (72 h; Pseudokirchneriella subcapitata; GLP)
Threshold limit - Algae [2]	> 97.2 mg/l (72 h; Pseudokirchneriella subcapitata; GLP)

12.2. Persistence and degradability

HIT-HY 200-R, A

Persistence and degradability	Not established.
-------------------------------	------------------

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)

Biodegradation	84 %
----------------	------

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)

Persistence and degradability	Readily biodegradable in water.
-------------------------------	---------------------------------

Quartz (SiO₂) (14808-60-7)

Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

12.3. Bioaccumulative potential

HIT-HY 200-R, A

Bioaccumulative potential	Not established.
---------------------------	------------------

1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)

Partition coefficient n-octanol/water (Log Kow)	2.1
---	-----

HIT-HY 200-R, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)

Partition coefficient n-octanol/water (Log Pow)	3.1
---	-----

2,2'-(m-tolylimino)diethanol (91-99-6)

Partition coefficient n-octanol/water (Log Pow)	1.9
---	-----

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)

Bioaccumulative potential	Low bioaccumulation potential (BCF < 500).
---------------------------	--

BCF - Fish [1]	≤ 100
----------------	-------

BCF - Fish [2]	3.2 Quantitative structure-activity relationship (QSAR)
----------------	---

Partition coefficient n-octanol/water (Log Pow)	0.97 (OECD 102 method)
---	------------------------

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.9 (log Koc, Calculated value)
--	---------------------------------

Quartz (SiO2) (14808-60-7)

Bioaccumulative potential	No bioaccumulation data available.
---------------------------	------------------------------------

12.4. Mobility in soil

1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)

Partition coefficient n-octanol/water (Log Kow)	2.1
---	-----

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)

Partition coefficient n-octanol/water (Log Pow)	3.1
---	-----

2,2'-(m-tolylimino)diethanol (91-99-6)

Partition coefficient n-octanol/water (Log Pow)	1.9
---	-----

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)

Ecology - soil	Highly mobile in soil.
----------------	------------------------

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.9 (log Koc, Calculated value)
--	---------------------------------

Partition coefficient n-octanol/water (Log Pow)	0.97 (OECD 102 method)
---	------------------------

Quartz (SiO2) (14808-60-7)

Surface tension	No data available in the literature
-----------------	-------------------------------------

Ecology - soil	Low potential for mobility in soil.
----------------	-------------------------------------

12.5. Other adverse effects

Ozone

Not classified

Other information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste)

Disposal must be done according to official regulations.

Product/Packaging disposal recommendations

After curing, the product can be disposed of with household waste.. Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials

Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

HIT-HY 200-R, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

ADR	IMDG	IATA	RID
14.1. UN number			
Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Rail transport

Not regulated

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)

Listed on the Canadian DSL (Domestic Substances List)

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)

Listed on the Canadian DSL (Domestic Substances List)

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)

Listed on the Canadian DSL (Domestic Substances List)

Quartz (SiO₂) (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

HIT-HY 200-R, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

2,2'-(m-tolylimino)diethanol (91-99-6)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Quartz (SiO₂) (14808-60-7)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

SECTION 16: Other information

SDS Major/Minor None
Issue date 12-20-2021
Revision date 12-20-2021
Supersedes 09-25-2018

Indication of changes:

Section	Changed item	Change	Comments
3.2	Composition/information on ingredients	Modified	

Other information None.

Full text of H-statements:

H300	Fatal if swallowed.
H301	Toxic if swallowed.
H312	Harmful in contact with skin.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H350	May cause cancer.
H412	Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms:

HIT-HY 200-R, A

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative

SDS_CA_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.