

Li-Ion Batteries <100 Wh

Product Safety Information Sheet

A safety data sheet is not required for this product. This Product Safety Information Sheet has been created on a voluntary basis
Issue date: 11/11/2024 Revision date: 11/11/2024 Supersedes: 04/17/2024 Version: 7.22

SECTION 1: Identification

1.1. Product identifier

Product form	Article
Product name	Li-Ion Batteries <100 Wh
Product code	BU ET&A
Other means of identification	Hilti B 7/1.5 Li-Ion (01), Hilti B 7/2.0 Li-Ion (01), Hilti B 7/2.5 Li-Ion (01), Hilti B 12/2.6 Li-Ion (01), Hilti B 12/4.0 Li-Ion (01), Hilti B 12-30 Li-Ion (01), Hilti B 12-55 Li-Ion (01), Hilti B 14/1.6 Li-Ion (01), Hilti B 14/2.6 Li-Ion (01), Hilti B 14/3.3 Li-Ion (01), Hilti B 14/5.2 Li-Ion (01), Hilti B 18/1.6 Li-Ion (01), Hilti B 18/2.6 Li-Ion (01), Hilti B 18/2.6 Li-Ion (02), Hilti B 18/3.3 Li-Ion (01), Hilti B 22/1.6 Li-Ion (01), Hilti B 22/2.6 Li-Ion (01), Hilti B 22/2.6 Li-Ion (02), Hilti B 22/3.0 Li-Ion (01), Hilti B 22/3.3 Li-Ion (01), Hilti B 22/4.0 Li-Ion (01), Hilti B 36/2.4 Li-Ion (01), Hilti B 36/2.6 Li-Ion (02), Hilti B 144/2.6 Li-Ion (01), Hilti B 22-55 Li-Ion (01), Hilti B 22-85 Li-Ion (01), Hilti B 22-100 Li-Ion (01)

1.2. Recommended use and restrictions on use

Recommended uses and restrictions	For professional use only
Recommended use	Rechargeable Lithium Ion battery for power tools

1.3. Supplier

Supplier	Department issuing data specification sheet
Hilti (Canada) Corp. 2201 Bristol Circle Suite 700 CA L6H 0J8 Oakville, Ontario Canada T +1905 8139200 1-800-363-4458 toll free, F +1 905 813 9009 ca-sales@hilti.com	Hilti AG Feldkircherstraße 100 FL 9494 Schaan Liechtenstein T +423 234 2111 product.compliance-power.tools@hilti.com

1.4. Emergency telephone number

Emergency number	Emergency CONTACT (24-Hour-Number) GBK/Infotrac ID 101022 (USA domestic) 1 800 535 5053 or international (001) 352 323 3500
------------------	--

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Not classified

2.2. GHS Label elements, including precautionary statements

GHS CA labelling

No labelling applicable



Li-Ion Batteries <100 Wh

Product Safety Information Sheet

A safety data sheet is not required for this product. This Product Safety Information Sheet has been created on a voluntary basis

2.3. Other hazards

Other hazards which do not result in classification

For the battery chemical materials are stored in a hermetically sealed metal case, designed to withstand temperatures and pressures encountered during normal use. As a result, during normal use there is no physical danger of ignition or explosion and chemical danger of hazardous materials leakage.

It may cause heat generation or electrolyte leakage if battery terminals contact with other metals. Electrolyte is flammable. In case of electrolyte leakage move the battery from fire immediately. However if exposed to a fire, added mechanical shocks, decomposed, added electric stress by miss-use, the gas release vent will be operated. The battery case will be breaked at the extreme, hazardous materials may be released.

Moreover, if heated strongly by a surrounding fire, acrid gas may be emitted.

2.4. Unknown acute toxicity (GHS CA)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

Li-Ion Batteries <100 Wh

Product Safety Information Sheet

A safety data sheet is not required for this product. This Product Safety Information Sheet has been created on a voluntary basis

3.2. Mixtures

Comments

Lithium Ion rechargeable battery pack:

Name/Type	Energy content (Wh)
B 7 / 1.5 Li-Ion (01)	10,80
B 7 / 2.0 Li-Ion (01)	14,40
B 7 / 2.5 Li-Ion (01)	18,00
B 12 / 2.6 Li-Ion (01)	28,10
B 12 / 4.0 Li-Ion (01)	42,66
B 12-30 Li-Ion (01)	27,00 / 28,10
B 12-55 Li-Ion (01)	54,00
B 14 / 1.6 Li-Ion (01)	23,00
B 14 / 2.6 Li-Ion (01)	36,00
B 14 / 3.3 Li-Ion (01)	48,00
B 14 / 5.2 Li-Ion (01)	73,40
B 18 / 1.6 Li-Ion (01)	34,60
B 18 / 2.6 Li-Ion (01)	56,20
B 18 / 2.6 Li-Ion (02)	56,20
B 18 / 3.3 Li-Ion (01)	71,30
B 22 / 1.6 Li-Ion (01)	34,60
B 22 / 2.6 Li-Ion (01)	56,20
B 22 / 2.6 Li-Ion (02)	56,20
B 22 / 3.0 Li-Ion (01)	64,80
B 22 / 3.3 Li-Ion (01)	71,30
B 22 / 4.0 Li-Ion (01)	86,40
B 36 / 2.6 Li-Ion (01)	93,60
B 36 / 2.6 Li-Ion (02)	93,60
B 144 / 2.6 Li-Ion (01)	37,44
B 22-55 Li-Ion (01)	54,00
B 22-85 Li-Ion (01)	85,32
B 22-100 Li-Ion (01)	97,2

This product contains a positive electrode (Lithium cobalt oxide (CAS-No. 12190-79-3)), a negative electrode (graphite (CAS-No. 7782-42-5)) and electrolyte (ethylene carbonate(CAS-No. 96-49-1), diethyl carbonate (CAS-No. 105-58-8) and lithium hexafluorophosphate (CAS-No. 21324-40-3)).

The physical form of the product, however, precludes exposure to workers under normal conditions of use.

This mixture does not contain any substances to be mentioned according to the criteria of schedule 1, item 3 of the Hazardous Products Regulations.

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.
First-aid measures general	If the electrolyte is leaking out of the battery pack, the following measures have to be taken.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	Not expected to present a significant hazard under anticipated conditions of normal use.
------------------	--

Li-Ion Batteries <100 Wh

Product Safety Information Sheet

A safety data sheet is not required for this product. This Product Safety Information Sheet has been created on a voluntary basis

Potential adverse human health effects and symptoms

This product contains an organic electrolyte. If the electrolyte is leaking out of the battery pack, the following effects are known when getting into contact: Irritation: severely irritant to eyes. Irritation: may cause irritation to the respiratory system.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media

Cool batteries and accumulators with water jet. In case of fire in the surroundings: Use extinguishing agent suitable for surrounding fire.

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media

No additional information available.

5.3. Specific hazards arising from the hazardous product

Hazardous decomposition products in case of fire

Formation of toxic gases is possible during heating or in case of fire.

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions

Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting

Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

No flames, no sparks. Eliminate all sources of ignition. Isolate from fire, if possible, without unnecessary risk.

6.2. Methods and materials for containment and cleaning up

Methods for cleaning up

Take up liquid spill into absorbent material.

Other information

Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

Do not soak in water or seawater.

Do not expose to strong oxidizers.

Do not give a strong mechanical shock or fling.

Never disassemble, modify or deform.

Do not connect the positive terminal to the negative terminal with electrically conductive material.

Use only the chargers / electric tools specified by Hilti to charge or discharge the battery.

Do not throw into fire or expose to high temperatures (>85 °C).

Do not connect the positive terminal to the negative terminal with electrically conductive material.

Always wash hands after handling the product.

Hygiene measures

Additional hazards when processed

Normal use of this product shall imply use in accordance with the instructions on the packaging and in line with the expectations of a professional user.

Li-Ion Batteries <100 Wh

Product Safety Information Sheet

A safety data sheet is not required for this product. This Product Safety Information Sheet has been created on a voluntary basis

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Avoid direct sunlight, high temperature, high humidity. Store in a cool place (temperature: -20 °C ~ 40 °C, humidity: 45 - 85%).
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.
Storage temperature	-20 – 40 °C
Storage area	Store in a well-ventilated place.
Information on mixed storage	Store away from water. Do not store together with electrically conductive materials.

The accu-pack should be stored at 30 to 50% of the charging capacity.
Avoid storing in places where it is exposed to static electricity.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional information	No technical measures are necessary during normal use. In case of leakage of substances contained within the cell, the information below may be useful.
------------------------	---

8.2. Appropriate engineering controls

Appropriate engineering controls	If the electrolyte is leaking out of the battery pack, the following measures have to be taken.
----------------------------------	---

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:				
Wear protective gloves.				
Type	Material	Permeation	Thickness (mm)	Penetration
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0,12	

Eye protection:				
Chemical goggles or safety glasses				

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	plastic case.



Li-Ion Batteries <100 Wh

Product Safety Information Sheet

A safety data sheet is not required for this product. This Product Safety Information Sheet has been created on a voluntary basis

Colour	red Black
Odour	odourless
Odour threshold	No data available
pH	No data available
Relative evaporation rate (butylacetate=1)	No data available
Relative evaporation rate (ether=1)	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	No data available
Flash point	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Flammability (solid, gas)	Non flammable.
Vapour pressure	No data available
Relative vapour density at 20°C	No data available
Relative density	No data available
Solubility	No data available
Partition coefficient n-octanol/water (Log Pow)	No data available
Viscosity, kinematic	No data available
Explosive properties	Risk of explosion by shock, friction, fire or other sources of ignition.
Explosive limits	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

Reactivity	No additional information available
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	Heating may cause a fire or explosion.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures. Water, humidity.
Incompatible materials	Conductive materials, water, seawater, strong oxidizers and strong acids.
Hazardous decomposition products	fume. Carbon monoxide. Carbon dioxide.
Hardening time:	No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified
Skin corrosion/irritation	Not classified
Serious eye damage/irritation	Not classified
Respiratory or skin sensitization	Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified



Li-Ion Batteries <100 Wh

Product Safety Information Sheet

A safety data sheet is not required for this product. This Product Safety Information Sheet has been created on a voluntary basis

Potential adverse human health effects and symptoms

Symptoms/effects
Other information

This product contains an organic electrolyte. If the electrolyte is leaking out of the battery pack, the following effects are known when getting into contact: Irritation: severely irritant to eyes. Irritation: may cause irritation to the respiratory system.
Not expected to present a significant hazard under anticipated conditions of normal use.
When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	Not classified
Hazardous to the aquatic environment, long-term (chronic)	Not classified

12.2. Persistence and degradability

Li-Ion Batteries <100 Wh	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Li-Ion Batteries <100 Wh	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone	Not classified
Other information	Do not allow battery packs to penetrate the soil. The battery cell may corrode and electrolyte may leak.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations	Dispose in a safe manner in accordance with local/national regulations. Refer to manufacturer/supplier for information on recovery/recycling.
Ecological information	Avoid release to the environment.

SECTION 14: Transport information

In accordance with TDG / DOT / IMDG / IATA

TDG	DOT	IMDG	IATA
14.1. UN number			
UN3480	3480	3480	3480
14.2. Proper Shipping Name			
LITHIUM ION BATTERIES	Lithium ion batteries	LITHIUM ION BATTERIES	Lithium ion batteries
14.3. Transport hazard class(es)			
9	9	9	9



Li-Ion Batteries <100 Wh

Product Safety Information Sheet

A safety data sheet is not required for this product. This Product Safety Information Sheet has been created on a voluntary basis

TDG	DOT	IMDG	IATA
			
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

14.6. Special precautions for user

TDG

UN-No. (TDG) : UN3480

Li-Ion Batteries <100 Wh

Product Safety Information Sheet

A safety data sheet is not required for this product. This Product Safety Information Sheet has been created on a voluntary basis

TDG Special Provisions

- : 34 - (1) These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of lithium cells and batteries on a road vehicle, a railway vehicle or a vessel on a domestic voyage if
- (a) for a lithium metal or lithium alloy cell, the lithium content is not more than 1 g, and, for a lithium-ion cell, the watt-hour rating is not more than 20 Wh;
 - (b) for a lithium metal or lithium alloy battery, the aggregate lithium content is not more than 2 g, and for a lithium-ion battery, the watt-hour rating is not more than 100 Wh;
 - (c) lithium ion batteries are marked with the watt-hour rating on the outside case, except for those manufactured before January 1, 2009;
 - (d) each cell and battery type passes each of the tests set out in paragraph 2.43.1(2)(a) of Part 2 (Classification);
 - (e) the cells and batteries are afforded protection against short circuit, including protection against contact with conductive materials within the same packaging that could lead to a short circuit;
 - (f) the cells and batteries are packed in a means of containment that completely encloses the cells and batteries;
 - (g) the gross mass of the cells and batteries does not exceed 30 kg, except when the cells and batteries are installed in or packed with equipment; and
 - (h) the cells and batteries are packed in a means of containment capable of withstanding a 1.2 m drop test in any orientation without damage to the cells or batteries contained inside the means of containment, without the contents shifting so as to allow battery-to-battery or cell-to-cell, contact, and without release of contents.
- (2) Cells and batteries referred to in subsection (1) that are installed in equipment must, unless they are afforded equivalent protection by the equipment in which they are contained,
- (a) be afforded protection against damage and short circuit, including protection against contact with conductive materials within the same packaging that could lead to a short circuit;
 - (b) subject to subsection (3), be fitted to prevent accidental activation; and
 - (c) be packed in a means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no release of the dangerous goods that could endanger public safety.
- (3) Paragraph (2)(b) does not apply to cells and batteries installed in devices that are intentionally active during transport such as radio frequency identification transmitters, watches and sensors, and that are not capable of generating a dangerous evolution of heat.
- (4) Except for means of containment containing button cell batteries installed in equipment, including circuit boards, or no more than four cells installed in equipment or no more than two batteries installed in equipment, each means of containment must be marked with the appropriate lithium battery mark in accordance with section 4.24.
- (5) Despite subsection (4), except for means of containment containing button cell batteries installed in equipment, including circuit boards, or no more than four cells installed in equipment or no more than two batteries installed in equipment, each means of containment may, until December 31, 2018, be marked with the following:
- (a) "lithium metal", "lithium métal", "lithium ion" or "lithium ionique", as appropriate;
 - (b) an indication that the means of containment must be handled with care and that a flammability hazard exists if the means of containment is damaged;
 - (c) an indication that special procedures must be followed in the event the means of containment is damaged, including inspection and repacking, if necessary; and
 - (d) a telephone number to call for additional information, 123 - (1) The testing requirements in subsection 38.3 of Part III of the Manual of Tests and Criteria do not apply to production runs consisting of not more than 100 cells and batteries or to pre-production prototypes of cells and batteries that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage if
- (a) the cells or batteries are imported, offered for transport, handled or transported in accordance with Packing Instruction P910 of the UN Recommendations; and



Li-Ion Batteries <100 Wh

Product Safety Information Sheet

A safety data sheet is not required for this product. This Product Safety Information Sheet has been created on a voluntary basis

- (b) the pre-production prototypes of cells and batteries are in transport for the purpose of testing.
- (2) Despite paragraph (1)(b), batteries that have a total mass of 12 kg or more and that have a strong, impact-resistant outer casing, or assemblies of them, may be packed in an outer means of containment or protective enclosure designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no release of the dangerous goods that could endanger public safety. The batteries or battery assemblies must be protected from short-circuit, 137 - (1) This shipping name applies to lithium ion cells or batteries, and lithium metal cells or batteries, that are damaged or defective and do not conform to subsection 2.43.1(2) of Part 2 (Classification).
- (2) Lithium ion cells or batteries and lithium metal cells or batteries that are damaged or defective, include, but are not limited to, cells or batteries that have leaked or vented, or have sustained physical or mechanical damage, and cannot be diagnosed prior to transport, or that have been identified as being defective for safety reasons.
- (3) Lithium ion cells or batteries and lithium metal cells or batteries that are damaged or defective must be packed in accordance with Packing Instructions P908 or LP904 of the UN Recommendations, as applicable.
- (4) As applicable, the outer means of containment or the overpack must be marked legibly and visibly on a contrasting background, with the words "Damaged/Defective Lithium Ion Batteries", "piles au lithium ionique endommagées/défectueuses", "Damaged/Defective Lithium Metal Batteries" or "piles au lithium métal endommagées/défectueuses".
- (5) It is forbidden to transport lithium ion cells or batteries and lithium metal cells or batteries that are damaged or defective and that, under normal conditions of transport, are liable to disassemble rapidly, react dangerously, produce a flame or a dangerous evolution of heat, or produce a dangerous emission of toxic, corrosive or flammable gases or vapours.
- (6) It is forbidden to transport by aircraft lithium ion cells or batteries and lithium metal cells or batteries that are damaged or defective, 138 - (1) When transported for disposal or recycling, lithium ion cells or batteries and lithium metal cells or batteries, or equipment containing those cells or batteries,
- (a) are not subject to subsection 2.43.1(2) of Part 2 (Classification);
- (b) must be packed in accordance with Packing Instructions P909 or LP904 of the UN Recommendations, as applicable, whether packed with or without non-lithium cells or batteries or equipment containing those cells or batteries;
- (c) must be in a means of containment or an overpack that is marked legibly and visibly on a contrasting background with the words "Lithium batteries for disposal", "Piles au lithium destinées à l'élimination", "Lithium batteries for recycling" or "Piles au lithium destinées au recyclage", as appropriate; and
- (d) are forbidden for transport by aircraft.
- (2) Damaged or defective cells and batteries must be offered for transport or transported under special provision 137, 149 - These dangerous goods are forbidden for transport as cargo on a passenger aircraft, 159 - (1) Subject to subsection (2), the label to be used for these dangerous goods is the one illustrated under the heading for lithium batteries "Class 9, Lithium Batteries" in the appendix to Part 4 (Dangerous Goods Safety Marks).
- (2) The generic Class 9 label may be used until December 31, 2018.

Explosive Limit and Limited Quantity Index	: 0
Excepted quantities (TDG)	: E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 5 kg
Emergency Response Guide (ERG) Number	: 147

DOT
UN-No.(DOT) : UN3480



Li-Ion Batteries <100 Wh

Product Safety Information Sheet

A safety data sheet is not required for this product. This Product Safety Information Sheet has been created on a voluntary basis

DOT Special Provisions (49 CFR 172.102)	: 388 - a. Lithium batteries containing both primary lithium metal cells and rechargeable lithium ion cells that are not designed to be externally charged, must meet the following conditions: i. The rechargeable lithium ion cells can only be charged from the primary lithium metal cells 422 - When labelling is required, the label to be used must be the label shown in §172.447. Labels conforming to requirements in place on December 31, 2016 may continue to be used until December 31, 2018. When a placard is displayed, the placard must be the placard shown in §172.560. A54 - Lithium batteries or lithium batteries contained or packed with equipment that exceed the maximum gross weight allowed by Column (9B) of the 172.101 Table may only be transported on cargo aircraft if approved by the Associate Administrator. A100 - Primary (non-rechargeable) lithium batteries and cells are forbidden for transport aboard passenger carrying aircraft. Secondary (rechargeable) lithium batteries and cells are authorized aboard passenger carrying aircraft in packages that do not exceed a gross weight of 5 kg.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 185
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 185
DOT Packaging Bulk (49 CFR 173.xxx)	: 185
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: Forbidden
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 35 kg
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

IMDG

Special provisions (IMDG)	: 188, 230, 310, 348, 376, 377, 384, 387
Limited quantities (IMDG)	: 0
Packing instructions (IMDG)	: P903, P908, P909, P910, P911, LP903, LP904, LP905, LP906
EmS-No. (Fire)	: F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage)	: S-I - SPILLAGE SCHEDULE India - FLAMMABLE SOLIDS (REPACKING POSSIBLE)
Stowage category (IMDG)	: A
Stowage and handling (IMDG)	: SW19
MFAG-No	: 147

IATA

PCA packing instructions (IATA)	: Forbidden
PCA max net quantity (IATA)	: Forbidden
CAO packing instructions (IATA)	: See 965
Special provisions (IATA)	: A88, A99, A154, A164, A183, A201, A213, A331, A334, A802

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

No additional information available

SECTION 16: Other information

A safety data sheet is not required for this product. This Product Safety Information Sheet has been created on a voluntary basis

Issue date	11-11-2024
Revision date	11-11-2024
Supersedes	04-17-2024



Li-Ion Batteries <100 Wh

Product Safety Information Sheet

A safety data sheet is not required for this product. This Product Safety Information Sheet has been created on a voluntary basis

Indication of changes			
Section	Changed item	Change	Comments
1.1	Product name	Added	
3.2	Comments	Added	

Other information

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory. All components of this product are listed, or excluded from listing, on the Canadian Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL).

SDS_CA_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.