

HIT-HY 200-R V3

Safety information for 2-Component-products

Issue date: 25/11/2025

Revision date: 25/11/2025

Supersedes: 28/07/2025

Version: 2.0

SECTION 1: Kit identification

1.1 Product identifier

Product name

HIT-HY 200-R V3



Product code

BU Anchor

1.2 Details of the supplier of the Safety information for 2-Component-products

Hilti (Canada) Corp.
2201 Bristol Circle
Suite 700
L6H 0J8 Oakville, Ontario - Canada
T +1905 8139200
1-800-363-4458 toll free - F +1 905 813 9009
ca-sales@hilti.com

SECTION 2: General information

Storage

Storage temperature : 5 - 25 °C

A SDS for each of these components is included. Please do not separate any component SDS from this cover page

This Kit should be handled in accordance with good laboratory practices and appropriate personal protective equipment should be used

SECTION 3: Kit contents

Classification of the Product

Classification (GHS CA)

Serious eye damage/eye irritation, Category 2 H319
Skin sensitization, Category 1 H317

Label elements

GHS CA labelling

Hazard pictograms (GHS CA)



GHS07

Signal word (GHS CA)

Warning

Hazardous ingredients

methacrylates, dibenzoyl peroxide

Hazard statements (GHS CA)

H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation

Precautionary statements (GHS CA)

P280 - Wear eye protection, protective clothing, protective gloves.
P262 - Do not get in eyes, on skin, or on clothing.

HIT-HY 200-R V3

Safety information for 2-Component-products


P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.
P337+P313 - If eye irritation persists: Get medical advice or attention.
P302+P352 - IF ON SKIN: Wash with plenty of water.

Additional information

2-Component-foilpack, contains:

Component A: Urethane methacrylate resin, inorganic filler

Component B: Dibenzoyl peroxide, phlegmatized



Name	General description	Quantity	Unit	Classification (GHS CA)
HIT-HY 200-R V3, A		1	pcs (pieces)	Skin Sens. 1, H317
HIT-HY 200-R V3, B		1	pcs (pieces)	Eye Irrit. 2A, H319 Skin Sens. 1, H317

SECTION 4: General advice

General advice

For professional users only

SECTION 5: Safe handling advice

General measures

Spilled material may present a slipping hazard

Environmental precautions

Prevent entry to sewers and public waters

Notify authorities if liquid enters sewers or public waters

Storage conditions

Keep cool. Protect from sunlight.

Precautions for safe handling

Wear personal protective equipment

Avoid contact with skin and eyes

Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work

Provide good ventilation in process area to prevent formation of vapour

Methods for cleaning up

This material and its container must be disposed of in a safe way, and as per local legislation

Mechanically recover the product

Store away from other materials.

For containment

Collect spillage.

Incompatible materials

Sources of ignition

Direct sunlight

Incompatible products

Strong bases

Strong acids

SECTION 6: First aid measures

First-aid measures after eye contact

Rinse immediately with plenty of water

Remove contact lenses, if present and easy to do. Continue rinsing.

Obtain medical attention if pain, blinking or redness persists

HIT-HY 200-R V3

Safety information for 2-Component-products

First-aid measures after ingestion	Rinse mouth Get medical advice/attention. Do not induce vomiting Obtain emergency medical attention
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air Allow the victim to rest
First-aid measures after skin contact	Wash contaminated clothing before reuse. Wash with plenty of water/... If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures general	Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person If you feel unwell, seek medical advice (show the label where possible)
Symptoms/effects after eye contact	May cause severe irritation
Symptoms/effects after skin contact	May cause an allergic skin reaction.
Other medical advice or treatment	Treat symptomatically

SECTION 7: Fire fighting measures

Firefighting instructions	Use water spray or fog for cooling exposed containers Exercise caution when fighting any chemical fire Prevent fire fighting water from entering the environment
Protection during firefighting	Self-contained breathing apparatus Do not enter fire area without proper protective equipment, including respiratory protection
Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide Carbon monoxide

SECTION 8: Other information

No data available

HIT-HY 200-R V3, A

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272
Issue date: 11/25/2025 Revision date: 11/25/2025 Supersedes: 07/28/2025

Version: 2.0

SECTION 1: Identification

1.1. Product identifier

Product form	Mixture
Product name	HIT-HY 200-R V3, A
Product code	BU Anchor

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use	Composite mortar component for fasteners in the construction industry
Restrictions on use	For professional use only

1.4. Supplier's details

Supplier

Hilti (Canada) Corp.
2201 Bristol Circle
Suite 700
CA L6H 0J8 Oakville, Ontario
Canada
T +1905 8139200
1-800-363-4458 toll free, F +1 905 813 9009
ca-sales@hilti.com

Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
DE 86916 Kaufering
Deutschland
T +49 8191 90-0
product.compliance-anchors@hilti.com

1.5. Emergency telephone number

Emergency number	Emergency CONTACT (24-Hour-Number) GBK/Infotrac ID 101022 (USA domestic) 1 800 535 5053 or international (001) 352 323 3500
------------------	--

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Full text of H-statements: see section 16		

2.2. GHS Label elements, including precautionary statements

GHS CA labelling

Hazard pictograms (GHS CA)



Signal word (GHS CA)

Warning

Hazard statements (GHS CA)

H317 - May cause an allergic skin reaction

Precautionary statements (GHS CA)

P280 - Wear eye protection, protective clothing, protective gloves.

P262 - Do not get in eyes, on skin, or on clothing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

HIT-HY 200-R V3, A

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

contact lenses, if present and easy to do. Continue rinsing.
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.
P337+P313 - If eye irritation persists: Get medical advice or attention.
P302+P352 - IF ON SKIN: Wash with plenty of water.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Quartz (SiO ₂)	quartz / quartz (SiO ₂)	CAS-No.: 14808-60-7	40 – 60	Carc. 1A, H350 STOT RE 1, H372
2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester	-	CAS-No.: 2082-81-7	10 – 25	Skin Sens. 1B, H317
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol	1,2-propanediol, 2-methyl, monomethacrylate / 2-propenoic acid, 2-methyl-, 2-hydroxymethylethyl ester	CAS-No.: 27813-02-1	5 – 10	Eye Irrit. 2A, H319 Skin Sens. 1, H317
Aluminium oxide	-	CAS-No.: 1344-28-1	0.1 – 1	Not classified
2,2'-(m-tolylimino)diethanol	-	CAS-No.: 91-99-6	0.1 – 1	Acute Tox. 3 (Oral), H301 Acute Tox. 4 (Dermal), H312 Eye Irrit. 2A, H319
Carbon black	-	CAS-No.: 1333-86-4	< 0.1	Not classified

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	Wash contaminated clothing before reuse. Wash with plenty of water/.... If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	Rinse mouth. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.
First-aid measures general	Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact	May cause an allergic skin reaction.
-------------------------------------	--------------------------------------

HIT-HY 200-R V3, A

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

Symptoms/effects after eye contact	May cause severe irritation.
Potential adverse human health effects and symptoms	No additional information available.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	Treat symptomatically.
-----------------------------------	------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	Water spray. Carbon dioxide. Dry powder. Foam. Sand.
Unsuitable extinguishing media	Do not use a heavy water stream.

5.2. Specific hazards arising from the hazardous product

Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide. Carbon monoxide.
--	--

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Spilled material may present a slipping hazard.
------------------	---

6.2. Methods and materials for containment and cleaning up

For containment	Collect spillage.
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. Store away from other materials.
Other information	Dispose of materials or solid residues at an authorized site.

For further information refer to section 8: "Exposure controls/personal protection", For further information refer to section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.
Hygiene measures	Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Keep cool. Protect from sunlight.
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.
Heat and ignition sources	Keep away from heat and direct sunlight.
Storage temperature	5 – 25 °C



HIT-HY 200-R V3, A

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

HIT-HY 200-R V3, A

Canada (Alberta) - Occupational Exposure Limits

Local name	Aluminum oxide (Alumina)
OEL TWA	10 mg/m ³
Regulatory reference	Alberta Regulation 191/2021

Canada (British Columbia) - Occupational Exposure Limits

Local name	Carbon black
OEL TWA	3 mg/m ³ Inhalable
Notations and remarks	IARC group 2B carcinogen
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)

Canada (Manitoba) - Occupational Exposure Limits

Local name	Carbon black
OEL TWA	3 mg/m ³ (I - Inhalable particulate matter)
Notations and remarks	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2024

Canada (New Brunswick) - Occupational Exposure Limits

Local name	Carbon black
OEL TWA	3 mg/m ³
Notations and remarks	Bronchitis

Canada (Newfoundland and Labrador) - Occupational Exposure Limits

Local name	Carbon black
OEL TWA	3 mg/m ³ (I - Inhalable particulate matter)
Notations and remarks	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2024

Canada (Nova Scotia) - Occupational Exposure Limits

Local name	Carbon black
OEL TWA	3 mg/m ³ (I - Inhalable particulate matter)
Notations and remarks	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2024

Canada (Northwest Territories) - Occupational Exposure Limits

Local name	Aluminum oxide
------------	----------------



HIT-HY 200-R V3, A

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

HIT-HY 200-R V3, A	
OEL TWA	10 mg/m ³
OEL STEL	20 mg/m ³
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Quartz (SiO ₂) (14808-60-7)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Silica-Crystalline: Quartz
OEL TWA	0.025 mg/m ³ Respirable particulate
Notations and remarks	Carcinogenicity A2
Regulatory reference	Alberta Regulation 191/2021
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Silica, Crystalline - alpha quartz
OEL TWA	0.025 mg/m ³ Respirable
Notations and remarks	ACGIH Carcinogenicity category A2; IARC group 1 carcinogen
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Silica, crystalline, quartz
OEL TWA	0.025 mg/m ³ (R - Respirable particulate matter)
Notations and remarks	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Regulatory reference	ACGIH 2025
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Silica, crystalline, quartz
OEL TWA	0.025 mg/m ³ (R - Respirable particulate matter)
Notations and remarks	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Regulatory reference	ACGIH 2025
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Silica, crystalline, quartz
OEL TWA	0.025 mg/m ³ (R - Respirable particulate matter)
Notations and remarks	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Regulatory reference	ACGIH 2025
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Silica - Crystalline: Quartz



HIT-HY 200-R V3, A

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

Quartz (SiO ₂) (14808-60-7)	
OEL TWA	0.05 mg/m ³ (respirable fraction)
Notations and remarks	Designated substance
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Aluminium oxide (1344-28-1)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Aluminum oxide (Alumina)
OEL TWA	10 mg/m ³
Regulatory reference	Alberta Regulation 191/2021
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Aluminum oxide
OEL TWA	10 mg/m ³
OEL STEL	20 mg/m ³
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Carbon black (1333-86-4)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Carbon black
OEL TWA	3.5 mg/m ³
Regulatory reference	Alberta Regulation 191/2021
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Carbon black
OEL TWA	3 mg/m ³ Inhalable
Notations and remarks	IARC group 2B carcinogen
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Carbon black
OEL TWA	3 mg/m ³ (I - Inhalable particulate matter)
Notations and remarks	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2023
Canada (New Brunswick) - Occupational Exposure Limits	
Local name	Carbon black
OEL TWA	3 mg/m ³
Notations and remarks	Bronchitis



HIT-HY 200-R V3, A

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

Carbon black (1333-86-4)

Canada (Newfoundland and Labrador) - Occupational Exposure Limits

Local name	Carbon black
OEL TWA	3 mg/m ³ (I - Inhalable particulate matter)
Notations and remarks	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2023

Canada (Nova Scotia) - Occupational Exposure Limits

Local name	Carbon black
OEL TWA	3 mg/m ³ (I - Inhalable particulate matter)
Notations and remarks	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2023

Canada (Northwest Territories) - Occupational Exposure Limits

Local name	Carbon black
OEL TWA	3.5 mg/m ³
OEL STEL	7 mg/m ³
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)

Additional information

The product has a pasty consistency. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Appropriate engineering controls

Appropriate engineering controls

Ensure adequate ventilation.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Safety glasses. Gloves. Protective clothing. Avoid all unnecessary exposure.

Hand protection:

The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

Type	Material	Permeation	Thickness (mm)	Penetration
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0,12	

Eye protection:

Wear security glasses which protect from splashes

Type	Field of application	Characteristics
Safety glasses	Droplet	clear

HIT-HY 200-R V3, A

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	Black
Odour	characteristic
Odour threshold	Not determined
pH	No data available
Relative evaporation rate (butylacetate=1)	No data available
Relative evaporation rate (ether=1)	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	No data available
Flash point	> 109 °C DIN EN ISO 1523
Auto-ignition temperature	Not self-igniting
Decomposition temperature	No data available
Flammability (solid, gas)	Flammable solid.
Vapour pressure	No data available
Relative vapour density at 20°C	No data available
Relative density	No data available
Density	1.8 g/ml AW 4.3.23
Solubility	Water: Not miscible
Partition coefficient n-octanol/water (Log Pow)	No data available
Viscosity, kinematic	27777.778 mm ² /s
Viscosity, dynamic	50 Pa·s HN-0333
Explosive properties	Product is not explosive.
Explosive limits	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

Reactivity	No additional information available
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	No additional information available.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures.
Incompatible materials	Strong acids. Strong bases.
Hazardous decomposition products	fume. Carbon monoxide. Carbon dioxide. Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	No additional information available

HIT-HY 200-R V3, A

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)

LD50 oral rat	10066 mg/kg
LD50 oral	10060 mg/kg
LD50 dermal rat	> 3000 mg/kg

Aluminium oxide (1344-28-1)

LD50 oral rat	> 15900 mg/kg
LC50 Inhalation - Rat	7.6 mg/l
LC50 Inhalation - Rat (Dust/Mist)	> 2.3 mg/l/4h (OECD 403 method)

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)

LD50 oral rat	> 5000 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; >=2000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	≥ 5000 mg/kg bodyweight (Rabbit; Experimental value)

2,2'-(m-tolylimino)diethanol (91-99-6)

LD50 oral rat	300 – 2000 mg/kg
LD50 dermal rat	> 2000 mg/kg

Carbon black (1333-86-4)

LD50 oral	> 8000 mg/kg
Skin corrosion/irritation	Not classified
Serious eye damage/irritation	Not classified
Respiratory or skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified

Quartz (SiO2) (14808-60-7)

IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	Known Human Carcinogens

Carbon black (1333-86-4)

IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	Not classified
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified

Quartz (SiO2) (14808-60-7)

STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
------------------------	---

Aspiration hazard	Not classified
-------------------	----------------



HIT-HY 200-R V3, A

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

HIT-HY 200-R V3, A	
Viscosity, kinematic	27777.778 mm ² /s
Potential adverse human health effects and symptoms	No additional information available.
Symptoms/effects after skin contact	May cause an allergic skin reaction.
Symptoms/effects after eye contact	May cause severe irritation.

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	Not classified
Hazardous to the aquatic environment, long-term (chronic)	Not classified

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
LC50 - Other aquatic organisms [1]	9.79 mg/l
ErC50 algae	9.79 mg/l
NOEC (chronic)	20 mg/l
NOEC chronic crustacea	5.09 mg/l
NOEC chronic algae	2.11 mg/l
NOEC (acute)	7.51 mg/l
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
LC50 - Fish [1]	493 mg/l (48 h; Leuciscus idus; GLP)
EC50 - Crustacea [1]	> 143 mg/l (48 h; Daphnia magna; GLP)
ErC50 algae	97.2 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
Threshold limit - Algae [1]	> 97.2 mg/l (72 h; Pseudokirchneriella subcapitata; GLP)
Threshold limit - Algae [2]	> 97.2 mg/l (72 h; Pseudokirchneriella subcapitata; GLP)

12.2. Persistence and degradability

HIT-HY 200-R V3, A	
Persistence and degradability	Not established.
Quartz (SiO ₂) (14808-60-7)	
Not rapidly degradable	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
Biodegradation	84 %



HIT-HY 200-R V3, A

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

Aluminium oxide (1344-28-1)	
Not rapidly degradable	
Persistence and degradability	Not applicable.
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
Not rapidly degradable	
Persistence and degradability	Readily biodegradable in water.

12.3. Bioaccumulative potential

HIT-HY 200-R V3, A	
Bioaccumulative potential	Not established.
Quartz (SiO ₂) (14808-60-7)	
Bioaccumulative potential	No bioaccumulation data available.
2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
Partition coefficient n-octanol/water (Log Pow)	3.1
Aluminium oxide (1344-28-1)	
Bioaccumulative potential	Not applicable.
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
Bioaccumulative potential	Low bioaccumulation potential (BCF < 500).
BCF - Fish [1]	≤ 100
BCF - Fish [2]	3.2 Quantitative structure-activity relationship (QSAR)
Partition coefficient n-octanol/water (Log Pow)	0.97 (OECD 102 method)
2,2'-(m-tolylimino)diethanol (91-99-6)	
Partition coefficient n-octanol/water (Log Pow)	1.9

12.4. Mobility in soil

Quartz (SiO ₂) (14808-60-7)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for mobility in soil.
2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
Ecology - soil	Highly mobile in soil.
Organic Carbon Normalized Adsorption Coefficient (Log K _{oc})	1.9 (log K _{oc} , Calculated value)
2,2'-(m-tolylimino)diethanol (91-99-6)	

12.5. Other adverse effects

Ozone	Not classified
Other information	Avoid release to the environment.



HIT-HY 200-R V3, A

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation

Product/Packaging disposal recommendations

Ecological waste information

Disposal must be done according to official regulations.

After curing, the product can be disposed of with household waste. Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.

Avoid release to the environment.

SECTION 14: Transport information

In accordance with TDG / DOT / IMDG / IATA

TDG	DOT	IMDG	IATA
14.1. UN number			
Not regulated for transport			
14.2. Proper Shipping Name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

14.6. Special precautions for user

TDG

Not regulated

DOT

Not regulated

IMDG

Not regulated

IATA

Not regulated

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable



HIT-HY 200-R V3, A

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

SECTION 15: Regulatory information

15.1. National regulations

HIT-HY 200-R V3, A

Canada DSL & NDSL Flags

All components of this product are listed, or excluded from listing, on the Canadian Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

Quartz (SiO₂) (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List)

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)

Listed on the Canadian DSL (Domestic Substances List)

Aluminium oxide (1344-28-1)

Listed on the Canadian DSL (Domestic Substances List)

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)

Listed on the Canadian DSL (Domestic Substances List)

2,2'-(m-tolylimino)diethanol (91-99-6)

Listed on the Canadian DSL (Domestic Substances List)

Carbon black (1333-86-4)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: Other information

SDS Major/Minor

None

Issue date

11-25-2025

Revision date

11-25-2025

Supersedes

07-28-2025

Indication of changes

Section	Changed item	Change	Comments
3.2	Composition/information on ingredients	Modified	

Other information

None.

Full text of hazard classes and H-statements:

H301	Toxic if swallowed
H312	Harmful in contact with skin
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation



HIT-HY 200-R V3, A

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

Full text of hazard classes and H-statements:

H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative

SDS_CA_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

HIT-HY 200-R V3, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272
Issue date: 11/25/2025 Revision date: 11/25/2025 Supersedes: 07/28/2025

Version: 2.0

SECTION 1: Identification

1.1. Product identifier

Product form	Mixture
Product name	HIT-HY 200-R V3, B
Product code	BU Anchor

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use	Composite mortar component for fasteners in the construction industry
Restrictions on use	For professional use only

1.4. Supplier's details

Supplier

Hilti (Canada) Corp.
2201 Bristol Circle
Suite 700
CA L6H 0J8 Oakville, Ontario
Canada
T +1905 8139200
1-800-363-4458 toll free, F +1 905 813 9009
ca-sales@hilti.com

Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
DE 86916 Kaufering
Deutschland
T +49 8191 90-0
product.compliance-anchors@hilti.com

1.5. Emergency telephone number

Emergency number	Emergency CONTACT (24-Hour-Number) GBK/Infotrac ID 101022 (USA domestic) 1 800 535 5053 or international (001) 352 323 3500
------------------	--

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Serious eye damage/eye irritation, Category 2A	H319	Causes serious eye irritation
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Full text of H-statements: see section 16		

2.2. GHS Label elements, including precautionary statements

GHS CA labelling

Hazard pictograms (GHS CA)



Signal word (GHS CA)

Warning

Hazard statements (GHS CA)

H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation

Precautionary statements (GHS CA)

P280 - Wear eye protection, protective clothing, protective gloves.



HIT-HY 200-R V3, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

P262 - Do not get in eyes, on skin, or on clothing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.
P337+P313 - If eye irritation persists: Get medical advice or attention.
P302+P352 - IF ON SKIN: Wash with plenty of water.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Quartz (SiO ₂)	quartz / quartz (SiO ₂)	CAS-No.: 14808-60-7	40 – 60	Carc. 1A, H350 STOT RE 1, H372
dibenzoyl peroxide	-	CAS-No.: 94-36-0	10 – 25	Org. Perox. B, H241 Eye Irrit. 2A, H319 Skin Sens. 1, H317

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	Wash contaminated clothing before reuse. Wash with plenty of water/.... If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	Rinse mouth. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.
First-aid measures general	Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact	May cause an allergic skin reaction.
Symptoms/effects after eye contact	May cause severe irritation.
Potential adverse human health effects and symptoms	No additional information available.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	Treat symptomatically.
-----------------------------------	------------------------

HIT-HY 200-R V3, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	Water spray. Carbon dioxide. Dry powder. Foam. Sand.
Unsuitable extinguishing media	Do not use a heavy water stream.

5.2. Specific hazards arising from the hazardous product

Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide. Carbon monoxide.
--	--

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Spilled material may present a slipping hazard.
------------------	---

6.2. Methods and materials for containment and cleaning up

For containment	Collect spillage.
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. Store away from other materials.
Other information	Dispose of materials or solid residues at an authorized site.

For further information refer to section 8: "Exposure controls/personal protection", For further information refer to section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.
Hygiene measures	Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Keep cool. Protect from sunlight.
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.
Heat and ignition sources	Keep away from heat and direct sunlight.
Storage temperature	5 – 25 °C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



HIT-HY 200-R V3, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

HIT-HY 200-R V3, B	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Benzoyl peroxide (Dibenzoyl peroxide)
OEL TWA	5 mg/m ³
Notations and remarks	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required.
Regulatory reference	Alberta Regulation 191/2021
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Benzoyl peroxide
OEL TWA	5 mg/m ³
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Benzoyl peroxide
OEL TWA	5 mg/m ³
Notations and remarks	TLV® Basis: URT & skin irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
Canada (New Brunswick) - Occupational Exposure Limits	
Local name	Benzoyl peroxide
OEL TWA	5 mg/m ³
Notations and remarks	URT & skin irr
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Benzoyl peroxide
OEL TWA	5 mg/m ³
Notations and remarks	TLV® Basis: URT & skin irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Benzoyl peroxide
OEL TWA	5 mg/m ³
Notations and remarks	TLV® Basis: URT & skin irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Benzoyl peroxide
OEL TWA	5 mg/m ³



HIT-HY 200-R V3, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

HIT-HY 200-R V3, B	
OEL STEL	10 mg/m ³
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Quartz (SiO ₂) (14808-60-7)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Silica-Crystalline: Quartz
OEL TWA	0.025 mg/m ³ Respirable particulate
Notations and remarks	Carcinogenicity A2
Regulatory reference	Alberta Regulation 191/2021
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Silica, Crystalline - alpha quartz
OEL TWA	0.025 mg/m ³ Respirable
Notations and remarks	ACGIH Carcinogenicity category A2; IARC group 1 carcinogen
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Silica, crystalline, quartz
OEL TWA	0.025 mg/m ³ (R - Respirable particulate matter)
Notations and remarks	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Regulatory reference	ACGIH 2025
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Silica, crystalline, quartz
OEL TWA	0.025 mg/m ³ (R - Respirable particulate matter)
Notations and remarks	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Regulatory reference	ACGIH 2025
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Silica, crystalline, quartz
OEL TWA	0.025 mg/m ³ (R - Respirable particulate matter)
Notations and remarks	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Regulatory reference	ACGIH 2025
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Silica - Crystalline: Quartz
OEL TWA	0.05 mg/m ³ (respirable fraction)



HIT-HY 200-R V3, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

Quartz (SiO ₂) (14808-60-7)	
Notations and remarks	Designated substance
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
dibenzoyl peroxide (94-36-0)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Benzoyl peroxide (Dibenzoyl peroxide)
OEL TWA	5 mg/m ³
Notations and remarks	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required.
Regulatory reference	Alberta Regulation 191/2021
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Benzoyl peroxide
OEL TWA	5 mg/m ³
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Benzoyl peroxide
OEL TWA	5 mg/m ³
Notations and remarks	TLV® Basis: URT & skin irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH
Canada (New Brunswick) - Occupational Exposure Limits	
Local name	Benzoyl peroxide
OEL TWA	5 mg/m ³
Notations and remarks	URT & skin irr
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Benzoyl peroxide
OEL TWA	5 mg/m ³
Notations and remarks	TLV® Basis: URT & skin irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Benzoyl peroxide
OEL TWA	5 mg/m ³
Notations and remarks	TLV® Basis: URT & skin irr. Notations: A4 (Not classifiable as a Human Carcinogen)

HIT-HY 200-R V3, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

dibenzoyl peroxide (94-36-0)	
Regulatory reference	ACGIH
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Benzoyl peroxide
OEL TWA	5 mg/m ³
OEL STEL	10 mg/m ³
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)

Additional information The product has a pasty consistency. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Appropriate engineering controls

Appropriate engineering controls Ensure good ventilation of the work station.
 Environmental exposure controls No specific measures are required provided the product is handled in accordance with the general rules of occupational hygiene and safety.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Safety glasses. Gloves. Protective clothing. Avoid all unnecessary exposure.

Hand protection:				
Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.				
Type	Material	Permeation	Thickness (mm)	Penetration
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0,12	

Eye protection:		
Wear security glasses which protect from splashes		
Type	Field of application	Characteristics
Safety glasses	Droplet	clear

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Solid
 Appearance Thixotropic paste.



HIT-HY 200-R V3, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

Colour	white
Odour	characteristic
Odour threshold	Not determined
pH	No data available
Relative evaporation rate (butylacetate=1)	No data available
Relative evaporation rate (ether=1)	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	No data available
Flash point	No data available
Auto-ignition temperature	Not self-igniting
Decomposition temperature	No data available
Flammability (solid, gas)	Flammable solid.
Vapour pressure	No data available
Relative vapour density at 20°C	No data available
Relative density	No data available
Density	1.9 g/ml AW 4.3.23
Solubility	Water: Not miscible
Partition coefficient n-octanol/water (Log Pow)	No data available
Viscosity, kinematic	21052.632 mm²/s
Viscosity, dynamic	40 Pa·s HN-0333
Explosive properties	Product is not explosive.
Explosive limits	No data available

9.2. Other information

SADT	65 °C
------	-------

SECTION 10: Stability and reactivity

Reactivity	No additional information available
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	No additional information available.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures.
Incompatible materials	Strong acids. Strong bases.
Hazardous decomposition products	fume. Carbon monoxide. Carbon dioxide. Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified
Skin corrosion/irritation	Not classified
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory or skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified

Quartz (SiO₂) (14808-60-7)

IARC group	1 - Carcinogenic to humans
------------	----------------------------



HIT-HY 200-R V3, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

Quartz (SiO ₂) (14808-60-7)	
National Toxicology Program (NTP) Status	Known Human Carcinogens
dibenzoyl peroxide (94-36-0)	
IARC group	3 - Not classifiable
Reproductive toxicity	Not classified
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified
Quartz (SiO ₂) (14808-60-7)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not classified
HIT-HY 200-R V3, B	
Viscosity, kinematic	21052.632 mm ² /s
Potential adverse human health effects and symptoms	No additional information available.
Symptoms/effects after skin contact	May cause an allergic skin reaction.
Symptoms/effects after eye contact	May cause severe irritation.

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	Not classified
Hazardous to the aquatic environment, long-term (chronic)	Not classified

dibenzoyl peroxide (94-36-0)	
LC50 - Fish [2]	0.0602 mg/l (96h; Oncorhynchus mykiss; ECHA)
EC50 - Crustacea [1]	0.11 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 algae	0.0711 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
NOEC chronic fish	0.001 mg/l
NOEC (acute)	0.0316 mg/l (96h; Oncorhynchus mykiss; ECHA)

12.2. Persistence and degradability

HIT-HY 200-R V3, B	
Persistence and degradability	Not established.
Quartz (SiO ₂) (14808-60-7)	
Not rapidly degradable	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)



HIT-HY 200-R V3, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

dibenzoyl peroxide (94-36-0)	
Persistence and degradability	Readily biodegradable in water. Not established. May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

HIT-HY 200-R V3, B	
Bioaccumulative potential	Not established.
Quartz (SiO ₂) (14808-60-7)	
Bioaccumulative potential	No bioaccumulation data available.
dibenzoyl peroxide (94-36-0)	
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).
Partition coefficient n-octanol/water (Log Pow)	3.71

12.4. Mobility in soil

Quartz (SiO ₂) (14808-60-7)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for mobility in soil.
dibenzoyl peroxide (94-36-0)	
Surface tension	No data available (test not performed)
Ecology - soil	Low potential for mobility in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)

12.5. Other adverse effects

Ozone	Not classified
Other information	Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation	Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.
Ecological waste information	Avoid release to the environment.

SECTION 14: Transport information





In accordance with TDG / DOT / IMDG / IATA

TDG	DOT	IMDG	IATA
		Special provision(s) applied : 969	Special provision(s) applied : A197

HIT-HY 200-R V3, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

TDG	DOT	IMDG	IATA
14.1. UN number			
UN3077	3077	3077	3077
14.2. Proper Shipping Name			
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	Environmentally hazardous substances, solid, n.o.s.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	Environmentally hazardous substance, solid, n.o.s.
14.3. Transport hazard class(es)			
9	9	9	9
			
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes
not restricted according ADR Special Provision SP375, IATA-DGR Special Provision A197 and IMDG-Code 2.10.2.7			

14.6. Special precautions for user

TDG

UN-No. (TDG)

UN3077



HIT-HY 200-R V3, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

TDG Special Provisions

16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the danger or dangers posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3).

(2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name:

- (a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S;
- (b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S;
- (c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S;
- (d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or
- (e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S.

(3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment:

- (a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or
- (b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS,99 - (1) Mixtures of solids that are not dangerous goods and liquids or solids that are UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S, or UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S, may be offered for transport, handled or transported as UN3077 if there is no visible liquid when the dangerous goods are loaded into a means of containment and during transport.

(2) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S, or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S, on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no release of the dangerous goods that could endanger public safety.

5 kg

E1

171

DOT

UN-No. (DOT)

UN3077

Explosive Limit and Limited Quantity Index
Excepted quantities (TDG)
Emergency Response Guide (ERG) Number



HIT-HY 200-R V3, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

DOT Special Provisions (49 CFR 172.102)

8 - A hazardous substance that is not a hazardous waste may be shipped under the shipping description "Other regulated substances, liquid or solid, n.o.s.", as appropriate. In addition, for solid materials, special provision B54 applies.

146 - This description may be used for a material that poses a hazard to the environment but does not meet the definition for a hazardous waste or a hazardous substance, as defined in 171.8 of this subchapter, or any hazard class as defined in Part 173 of this subchapter, if it is designated as environmentally hazardous by the Competent Authority of the country of origin, transit or destination.

335 - Mixtures of solids that are not subject to this subchapter and environmentally hazardous liquids or solids may be classified as "Environmentally hazardous substances, solid, n.o.s." UN3077 and may be transported under this entry, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each transport unit must be leakproof when used as bulk packaging.

384 - For transportation by motor vehicle, substances meeting the conditions for high viscosity flammable liquids as prescribed in §173.121(b)(1)(i), (b)(1)(ii), and (b)(1)(iv) of this subchapter, may be reassigned to Packing Group III under the following conditions:

A112 - Notwithstanding the quantity limits shown in Column (9A) and (9B) for this entry, the following IBCs are authorized for transportation aboard passenger and cargo-only aircraft. Each IBC may not exceed a maximum net quantity of 1,000 kg:

a. Metal: 11A, 11B, 11N, 21A, 21B and 21N

b. Rigid plastics: 11H1, 11H2, 21H1 and 21H2

c. Composite with plastic inner receptacle: 11HZ1, 11HZ2, 21HZ1 and 21HZ2

d. Fiberboard: 11G

e. Wooden: 11C, 11D and 11F (with inner liners)

f. Flexible: 13H2, 13H3, 13H4, 13H5, 13L2, 13L3, 13L4, 13M1 and 13M2 (flexible IBCs must be sift-proof and water resistant or must be fitted with a sift-proof and water resistant liner).

B54 - Open-top, sift-proof rail cars are also authorized.

B120 - The use of flexible bulk containers conforming to the requirements in subpart R and subpart S of part 178 of this subchapter is permitted.

IB8 - Authorized IBCs: Metal (11A, 11B, 11N, 21A, 21B, 21N, 31A, 31B and 31N); Rigid plastics (11H1, 11H2, 21H1, 21H2, 31H1 and 31H2); Composite (11HZ1, 11HZ2, 21HZ1, 21HZ2, 31HZ1 and 31HZ2); Fiberboard (11G); Wooden (11C, 11D and 11F); Flexible (13H1, 13H2, 13H3, 13H4, 13H5, 13L1, 13L2, 13L3, 13L4, 13M1 or 13M2).

IP3 - Flexible IBCs must be sift-proof and water-resistant or must be fitted with a sift-proof and water-resistant liner.

N20 - A 5M1 multi-wall paper bag is authorized if transported in a closed transport vehicle.

N91 - The use of a non specification sift-proof, non-bulk, metal can with or without lid, or a non specification sift-proof, non-bulk fiber drum, with or without lid is authorized when transporting coal tar pitch compounds by motor vehicle or rail freight. The fiber drum must be fabricated with a three ply wall, as a minimum. The coal tar pitch compound must be in a solid mass during transportation.

T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2)

TP33 - The portable tank instruction assigned for this substance applies for granular and powdered solids and for solids which are filled and discharged at temperatures above their melting point which are cooled and transported as a solid mass. Solid substances transported or offered for transport above their melting point are authorized for transportation in portable tanks conforming to the provisions of portable tank instruction T4 for solid substances of packing group III or T7 for solid substances of packing group II, unless a tank with more stringent requirements for minimum shell thickness, maximum allowable working pressure, pressure-relief devices or bottom outlets are assigned in which case the more stringent tank instruction and special provisions shall apply. Filling limits must be in accordance with portable tank special provision TP3. Solids meeting the definition of an elevated temperature material must be transported in accordance with the applicable requirements of this subchapter.

DOT Packaging Exceptions (49 CFR 173.xxx)

155



HIT-HY 200-R V3, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

DOT Packaging Non Bulk (49 CFR 173.xxx)	213
DOT Packaging Bulk (49 CFR 173.xxx)	240
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	No Limit
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	No Limit
DOT Vessel Stowage Location	A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

IMDG

Special provisions (IMDG)	274, 335, 375, 966, 967, 969
Limited quantities (IMDG)	5 kg
Packing instructions (IMDG)	LP02, P002
EmS-No. (Fire)	F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage)	S-F - SPILLAGE SCHEDULE Foxtrot - WATER-SOLUBLE MARINE POLLUTANTS
Stowage category (IMDG)	A
Stowage and handling (IMDG)	SW23

IATA

PCA packing instructions (IATA)	956
PCA max net quantity (IATA)	400kg
CAO packing instructions (IATA)	956
Special provisions (IATA)	A97, A158, A179, A197, A215

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

HIT-HY 200-R V3, B	
Canada DSL & NDSL Flags	All components of this product are listed, or excluded from listing, on the Canadian Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

Quartz (SiO₂) (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List)

dibenzoyl peroxide (94-36-0)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: Other information

SDS Major/Minor	None
Issue date	11-25-2025
Revision date	11-25-2025
Supersedes	07-28-2025



HIT-HY 200-R V3, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

Indication of changes			
Section	Changed item	Change	Comments
3.2	Composition/information on ingredients	Modified	

Other information: None.

Full text of hazard classes and H-statements:	
H241	Heating may cause a fire or explosion
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet



HIT-HY 200-R V3, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

Abbreviations and acronyms:	
vPvB	Very Persistent and Very Bioaccumulative

SDS_CA_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.