

HIT-HY 100

Safety information for 2-Component-products

Issue date: 05/12/2025

Revision date: 05/12/2025

Supersedes: 28/07/2025

Version: 4.0

SECTION 1: Kit identification

1.1 Product identifier

Trade name

HIT-HY 100



Product code

BU Anchor

1.2 Details of the supplier of the Safety information for 2-Component-products

Hilti (Canada) Corp.
2201 Bristol Circle
Suite 700
L6H 0J8 Oakville, Ontario - Canada
T +1905 8139200
1-800-363-4458 toll free - F +1 905 813 9009
ca-sales@hilti.com

SECTION 2: General information

Storage

Storage temperature : 5 - 25 °C

A SDS for each of these components is included. Please do not separate any component SDS from this cover page

This Kit should be handled in accordance with good laboratory practices and appropriate personal protective equipment should be used

SECTION 3: Kit contents

Classification of the Product

Classification (GHS CA)

Serious eye damage/eye irritation, Category 2A	H319
Skin sensitization, Category 1	H317
Reproductive toxicity, Category 1B	H360

Label elements

GHS CA labelling

Hazard pictograms (GHS CA)



GHS07

GHS08

Signal word (GHS CA)

Danger

Hazardous ingredients

methacrylates, dibenzoyl peroxide, boric acid

Hazard statements (GHS CA)

H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H360 - May damage fertility or the unborn child

HIT-HY 100

Safety information for 2-Component-products

Precautionary statements (GHS CA)


P280 - Wear eye protection, protective clothing, protective gloves.
 P262 - Do not get in eyes, on skin, or on clothing.
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.
 P337+P313 - If eye irritation persists: Get medical advice or attention.
 P302+P352 - IF ON SKIN: Wash with plenty of water.

Additional information

2-Component-foilpack, contains:

Component A: Urethane methacrylate resin, inorganic filler

Component B: Dibenzoyl peroxide, phlegmatized



Name	General description	Quantity	Unit	Classification (GHS CA)
HIT-HY 100, A		1	pcs (pieces)	Eye Irrit. 2A, H319 Skin Sens. 1, H317 Repr. 1B, H360
HIT-HY 100, B		1	pcs (pieces)	Skin Sens. 1, H317

SECTION 4: General advice

General advice

For professional users only

SECTION 5: Safe handling advice

General measures

Spilled material may present a slipping hazard

Environmental precautions

Prevent entry to sewers and public waters
 Notify authorities if liquid enters sewers or public waters

Storage conditions

Keep cool. Protect from sunlight.

Precautions for safe handling

Wear personal protective equipment
 Avoid contact with skin and eyes
 Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work
 Provide good ventilation in process area to prevent formation of vapour

Methods for cleaning up

This material and its container must be disposed of in a safe way, and as per local legislation
 Mechanically recover the product
 Store away from other materials.

For containment

Collect spillage.

Incompatible materials

Sources of ignition
 Direct sunlight

Incompatible products

Strong bases
 Strong acids

SECTION 6: First aid measures

First-aid measures after eye contact

Rinse immediately with plenty of water
 Remove contact lenses, if present and easy to do. Continue rinsing.

HIT-HY 100

Safety information for 2-Component-products

First-aid measures after ingestion	Obtain medical attention if pain, blinking or redness persists Rinse mouth Get medical advice/attention. Do not induce vomiting Obtain emergency medical attention
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air Allow the victim to rest
First-aid measures after skin contact	Wash contaminated clothing before reuse. Wash with plenty of water/... If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures general	Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person If you feel unwell, seek medical advice (show the label where possible)
Symptoms/effects after eye contact	May cause severe irritation
Symptoms/effects after skin contact	May cause an allergic skin reaction.
Other medical advice or treatment	Treat symptomatically

SECTION 7: Fire fighting measures

Firefighting instructions	Use water spray or fog for cooling exposed containers Exercise caution when fighting any chemical fire Prevent fire fighting water from entering the environment
Protection during firefighting	Self-contained breathing apparatus Do not enter fire area without proper protective equipment, including respiratory protection
Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide Carbon monoxide

SECTION 8: Other information

No data available

HIT-HY 100, A

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272
Issue date: 12/05/2025 Revision date: 12/05/2025 Supersedes: 07/28/2025

Version: 4.0

SECTION 1: Identification

1.1. Product identifier

Product form	Mixture
Product name	HIT-HY 100, A
Product code	BU Anchor

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use For professional use only

1.4. Supplier's details

Supplier

Hilti (Canada) Corp.
2201 Bristol Circle
Suite 700
CA L6H 0J8 Oakville, Ontario
Canada
T +1905 8139200
1-800-363-4458 toll free, F +1 905 813 9009
ca-sales@hilti.com

Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
DE 86916 Kaufering
Deutschland
T +49 8191 90-0
product.compliance-anchors@hilti.com

1.5. Emergency telephone number

Emergency number Emergency CONTACT (24-Hour-Number)
GBK/Infotrac ID 101022
(USA domestic) 1 800 535 5053
or international (001) 352 323 3500

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Serious eye damage/eye irritation, Category 2A	H319	Causes serious eye irritation
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Reproductive toxicity, Category 1B	H360	May damage fertility or the unborn child
Full text of H-statements: see section 16		

2.2. GHS Label elements, including precautionary statements

GHS CA labelling

Hazard pictograms (GHS CA)



Signal word (GHS CA)

Danger

Hazard statements (GHS CA)

H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H360 - May damage fertility or the unborn child



HIT-HY 100, A

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

Precautionary statements (GHS CA)

P280 - Wear eye protection, protective clothing, protective gloves.

P262 - Do not get in eyes, on skin, or on clothing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.

P337+P313 - If eye irritation persists: Get medical advice or attention.

P302+P352 - IF ON SKIN: Wash with plenty of water.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Quartz (SiO ₂)	quartz / quartz (SiO ₂)	CAS-No.: 14808-60-7	25 – 40	Carc. 1A, H350 STOT RE 1, H372
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol	1,2-propanediol, 2-methyl, monomethacrylate / 2-propenoic acid, 2-methyl-, 2-hydroxymethylethyl ester	CAS-No.: 27813-02-1	5 – 10	Eye Irrit. 2A, H319 Skin Sens. 1, H317
2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester	-	CAS-No.: 2082-81-7	5 – 10	Skin Sens. 1B, H317
Aluminium oxide	-	CAS-No.: 1344-28-1	0.1 – 1	Not classified



HIT-HY 100, A

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
boric acid	boric acid basilit B / boracic acid / boric acid / boric acid (H3-BO3) / borofax / boron trihydroxide / dr.'s 1 flea terminator DF / dr.'s 1 flea terminator DFPBO / dr.'s 1 flea terminator DT / dr.'s 1 flea terminator DTPBO / E284 / epa pesticide code 011001 / flea prufe / LUCHEM AT / OPTIBOR NF / OPTIBOR SP / OPTIBOR SQ / OPTIBOR TG / OPTIBOR TP / orthoboric acid / ortho-boric acid / sassolite / super flea eliminator / three elephant / trihydroxyborone	CAS-No.: 10043-35-3	0.3 – 1	Repr. 1B, H360
4-tert-butylpyrocatechol	(dimethyl-1,1 ethyl)-4 dihydroxy-1,2 benzene / 1,2-Benzenediol, 4-(1,1-dimethylethyl)- / 4-(1,1-dimethylethyl)-1,2-benzenediol / 4-tert-butylpyrocatechol	CAS-No.: 98-29-3	0.1 – 1	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Skin Sens. 1, H317
Carbon black	-	CAS-No.: 1333-86-4	< 0.1	Not classified

Full text of hazard classes and H-statements : see section 16

HIT-HY 100, A

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	Wash contaminated clothing before reuse. Wash with plenty of water/.... If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	Rinse mouth. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.
First-aid measures general	Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact	May cause an allergic skin reaction.
Symptoms/effects after eye contact	May cause severe irritation.
Potential adverse human health effects and symptoms	No additional information available.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	Treat symptomatically.
-----------------------------------	------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	Water spray. Carbon dioxide. Dry powder. Foam. Sand.
Unsuitable extinguishing media	Do not use a heavy water stream.

5.2. Specific hazards arising from the hazardous product

Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide. Carbon monoxide.
--	--

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Spilled material may present a slipping hazard.
------------------	---

6.2. Methods and materials for containment and cleaning up

For containment	Collect spillage.
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. Store away from other materials.
Other information	Dispose of materials or solid residues at an authorized site.

For further information refer to section 8: "Exposure controls/personal protection", For further information refer to section 13



HIT-HY 100, A

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.
Hygiene measures	Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Keep cool. Protect from sunlight.
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.
Heat and ignition sources	Keep away from heat and direct sunlight.
Storage temperature	5 – 25 °C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

HIT-HY 100, A	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Carbon black
OEL TWA	3.5 mg/m ³
Regulatory reference	Alberta Regulation 191/2021
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Borate compounds, inorganic
OEL TWA	2 mg/m ³ Inhalable
OEL STEL	6 mg/m ³
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Boric acid
OEL TWA	2 mg/m ³ (I - Inhalable particulate matter)
OEL STEL	6 mg/m ³ (I - Inhalable particulate matter)
Notations and remarks	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
Canada (New Brunswick) - Occupational Exposure Limits	
Local name	Carbon black
OEL TWA	3 mg/m ³
Notations and remarks	Bronchitis



HIT-HY 100, A

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

HIT-HY 100, A	
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Boric acid
OEL TWA	2 mg/m ³ (I - Inhalable particulate matter)
OEL STEL	6 mg/m ³ (I - Inhalable particulate matter)
Notations and remarks	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Boric acid
OEL TWA	2 mg/m ³ (I - Inhalable particulate matter)
OEL STEL	6 mg/m ³ (I - Inhalable particulate matter)
Notations and remarks	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Borate compounds, inorganic
OEL TWA	2 mg/m ³ (inhalable fraction)
OEL STEL	6 mg/m ³ (inhalable fraction)
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Aluminium oxide (1344-28-1)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Aluminum oxide (Alumina)
OEL TWA	10 mg/m ³
Regulatory reference	Alberta Regulation 191/2021
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Aluminum oxide
OEL TWA	10 mg/m ³
OEL STEL	20 mg/m ³
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Quartz (SiO ₂) (14808-60-7)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Silica-Crystalline: Quartz
OEL TWA	0.025 mg/m ³ Respirable particulate
Notations and remarks	Carcinogenicity A2



HIT-HY 100, A

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

Quartz (SiO ₂) (14808-60-7)	
Regulatory reference	Alberta Regulation 191/2021
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Silica, Crystalline - alpha quartz
OEL TWA	0.025 mg/m ³ Respirable
Notations and remarks	ACGIH Carcinogenicity category A2; IARC group 1 carcinogen
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Silica, crystalline, quartz
OEL TWA	0.025 mg/m ³ (R - Respirable particulate matter)
Notations and remarks	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Regulatory reference	ACGIH 2025
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Silica, crystalline, quartz
OEL TWA	0.025 mg/m ³ (R - Respirable particulate matter)
Notations and remarks	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Regulatory reference	ACGIH 2025
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Silica, crystalline, quartz
OEL TWA	0.025 mg/m ³ (R - Respirable particulate matter)
Notations and remarks	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Regulatory reference	ACGIH 2025
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Silica - Crystalline: Quartz
OEL TWA	0.05 mg/m ³ (respirable fraction)
Notations and remarks	Designated substance
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Carbon black (1333-86-4)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Carbon black
OEL TWA	3.5 mg/m ³
Regulatory reference	Alberta Regulation 191/2021



HIT-HY 100, A

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

Relative density	No data available
Density	1.74 g/ml DIN 66137-2
Solubility	Water: Not miscible
Partition coefficient n-octanol/water (Log Pow)	No data available
Viscosity, kinematic	40.23 mm ² /s
Viscosity, dynamic	70 HN-0333
Explosive properties	Product is not explosive.
Explosive limits	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

Reactivity	No additional information available
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	No additional information available.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures.
Incompatible materials	Strong acids. Strong bases.
Hazardous decomposition products	fume. Carbon monoxide. Carbon dioxide. Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

Aluminium oxide (1344-28-1)	
LD50 oral rat	> 15900 mg/kg
LC50 Inhalation - Rat	7.6 mg/l
LC50 Inhalation - Rat (Dust/Mist)	> 2.3 mg/l/4h (OECD 403 method)
boric acid (10043-35-3)	
LD50 oral rat	2660 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; >2600 mg/kg bodyweight; Rat; Experimental value)
LD50 oral	2660 mg/kg
LD50 dermal rabbit	> 2000 mg/kg Rabbit; Experimental value; FIFRA (40 CFR)
LD50 dermal	2500 mg/kg
2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
LD50 oral rat	10066 mg/kg
LD50 oral	10060 mg/kg
LD50 dermal rat	> 3000 mg/kg
4-tert-butylpyrocatechol (98-29-3)	
LD50 oral rat	815 mg/kg bodyweight (Rat; Lethal; ECHA)



HIT-HY 100, A

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

4-tert-butylpyrocatechol (98-29-3)	
LD50 oral	2820 mg/kg
LD50 dermal rat	1331 mg/kg bodyweight (Rat;Lethal; ECHA)
LD50 dermal	630 mg/kg
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
LD50 oral rat	> 5000 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; >=2000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	≥ 5000 mg/kg bodyweight (Rabbit; Experimental value)
Carbon black (1333-86-4)	
LD50 oral	> 8000 mg/kg
Skin corrosion/irritation	Not classified
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory or skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Quartz (SiO ₂) (14808-60-7)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	Known Human Carcinogens
Carbon black (1333-86-4)	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	May damage fertility or the unborn child.
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified
Quartz (SiO ₂) (14808-60-7)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not classified
HIT-HY 100, A	
Viscosity, kinematic	40.23 mm ² /s
Potential adverse human health effects and symptoms	No additional information available.
Symptoms/effects after skin contact	May cause an allergic skin reaction.
Symptoms/effects after eye contact	May cause severe irritation.

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) Not classified

Hazardous to the aquatic environment, long-term (chronic) Not classified

boric acid (10043-35-3)	
LC50 - Fish [1]	447 mg/l



HIT-HY 100, A

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

boric acid (10043-35-3)	
LC50 - Fish [2]	79 ppm (96 h; Salmo gairdneri (Oncorhynchus mykiss); Hard water)
EC50 - Crustacea [1]	658 – 875 mg/l (48 h; Daphnia magna)
EC50 - Crustacea [2]	19.7 mg/l (336 h; Daphnia magna)
ErC50 algae	290 mg/l
NOEC chronic fish	2.1 mg/l
2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
LC50 - Other aquatic organisms [1]	9.79 mg/l
ErC50 algae	9.79 mg/l
NOEC (chronic)	20 mg/l
NOEC chronic crustacea	5.09 mg/l
NOEC chronic algae	2.11 mg/l
NOEC (acute)	7.51 mg/l
4-tert-butylpyrocatechol (98-29-3)	
LC50 - Fish [1]	0.12 mg/l (96 h, Danio rerio, Lethal, ECHA)
ErC50 algae	10.17 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
LC50 - Fish [1]	493 mg/l (48 h; Leuciscus idus; GLP)
EC50 - Crustacea [1]	> 143 mg/l (48 h; Daphnia magna; GLP)
ErC50 algae	97.2 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
Threshold limit - Algae [1]	> 97.2 mg/l (72 h; Pseudokirchneriella subcapitata; GLP)
Threshold limit - Algae [2]	> 97.2 mg/l (72 h; Pseudokirchneriella subcapitata; GLP)

12.2. Persistence and degradability

HIT-HY 100, A	
Persistence and degradability	Not established.
Aluminium oxide (1344-28-1)	
Not rapidly degradable	
Persistence and degradability	Not applicable.
Quartz (SiO ₂) (14808-60-7)	
Not rapidly degradable	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)



HIT-HY 100, A

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
Biodegradation	84 %
4-tert-butylpyrocatechol (98-29-3)	
Not rapidly degradable	
Persistence and degradability	Not readily biodegradable in water.
ThOD	2.4 g O ₂ /g substance
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
Not rapidly degradable	
Persistence and degradability	Readily biodegradable in water.

12.3. Bioaccumulative potential

HIT-HY 100, A	
Bioaccumulative potential	Not established.
Aluminium oxide (1344-28-1)	
Bioaccumulative potential	Not applicable.
Quartz (SiO ₂) (14808-60-7)	
Bioaccumulative potential	No bioaccumulation data available.
boric acid (10043-35-3)	
Bioaccumulative potential	Low bioaccumulation potential (BCF < 500).
BCF - Fish [2]	< 0.1 (60 days; Oncorhynchus tshawytscha; Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	-1.09 (Experimental value; EU Method A.8: Partition Coefficient; 22 °C)
2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
Partition coefficient n-octanol/water (Log Pow)	3.1
4-tert-butylpyrocatechol (98-29-3)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Partition coefficient n-octanol/water (Log Pow)	1.98 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
Bioaccumulative potential	Low bioaccumulation potential (BCF < 500).
BCF - Fish [1]	≤ 100
BCF - Fish [2]	3.2 Quantitative structure-activity relationship (QSAR)
Partition coefficient n-octanol/water (Log Pow)	0.97 (OECD 102 method)

12.4. Mobility in soil

Quartz (SiO ₂) (14808-60-7)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for mobility in soil.



HIT-HY 100, A

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

boric acid (10043-35-3)	
Surface tension	No data available in the literature
Ecology - soil	No (test)data on mobility of the substance available. May be harmful to plant growth, blooming and fruit formation.
2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
4-tert-butylpyrocatechol (98-29-3)	
Surface tension	No data available (test not performed)
Ecology - soil	Highly mobile in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.37 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
Ecology - soil	Highly mobile in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.9 (log Koc, Calculated value)

12.5. Other adverse effects

Ozone	Not classified
Other information	Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation	Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.
Ecological waste information	Avoid release to the environment.

SECTION 14: Transport information

In accordance with TDG / DOT / IMDG / IATA

	TDG	DOT	IMDG	IATA
14.1. UN number	Not applicable	Not applicable	Not applicable	Not applicable
14.2. Proper Shipping Name	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group	Not applicable	Not applicable	Not applicable	Not applicable



HIT-HY 100, A

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

TDG	DOT	IMDG	IATA
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

14.6. Special precautions for user

TDG

No data available

DOT

No data available

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

HIT-HY 100, A

Canada DSL & NDSL Flags

All components of this product are listed, or excluded from listing, on the Canadian Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

Aluminium oxide (1344-28-1)

Listed on the Canadian DSL (Domestic Substances List)

Quartz (SiO₂) (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List)

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)

Listed on the Canadian DSL (Domestic Substances List)

4-tert-butylpyrocatechol (98-29-3)

Listed on the Canadian DSL (Domestic Substances List)

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)

Listed on the Canadian DSL (Domestic Substances List)



HIT-HY 100, A

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

Carbon black (1333-86-4)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: Other information

Issue date 12-05-2025
Revision date 12-05-2025
Supersedes 07-28-2025

Other information None.

Full text of hazard classes and H-statements:

H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H350	May cause cancer.
H360	May damage fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure.

SDS_CA_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

HIT-HY 100, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272
Issue date: 12/05/2025 Revision date: 12/05/2025 Supersedes: 07/28/2025

Version: 4.0

SECTION 1: Identification

1.1. Product identifier

Product form	Mixture
Product name	HIT-HY 100, B
Product code	BU Anchor

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use	For professional use only
-----------------	---------------------------

1.4. Supplier's details

Supplier

Hilti (Canada) Corp.
2201 Bristol Circle
Suite 700
CA L6H 0J8 Oakville, Ontario
Canada
T +1905 8139200
1-800-363-4458 toll free, F +1 905 813 9009
ca-sales@hilti.com

Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
DE 86916 Kaufering
Deutschland
T +49 8191 90-0
product.compliance-anchors@hilti.com

1.5. Emergency telephone number

Emergency number	Emergency CONTACT (24-Hour-Number) GBK/Infotrac ID 101022 (USA domestic) 1 800 535 5053 or international (001) 352 323 3500
------------------	--

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Skin sensitization, Category 1	H317	May cause an allergic skin reaction
--------------------------------	------	-------------------------------------

Full text of H-statements: see section 16

2.2. GHS Label elements, including precautionary statements

GHS CA labelling

Hazard pictograms (GHS CA)



Signal word (GHS CA)

Warning

Hazard statements (GHS CA)

H317 - May cause an allergic skin reaction

Precautionary statements (GHS CA)

P280 - Wear eye protection, protective clothing, protective gloves.

P262 - Do not get in eyes, on skin, or on clothing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.



HIT-HY 100, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.

P337+P313 - If eye irritation persists: Get medical advice or attention.

P302+P352 - IF ON SKIN: Wash with plenty of water.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Quartz (SiO ₂)	quartz / quartz (SiO ₂)	CAS-No.: 14808-60-7	40 – 60	Carc. 1A, H350 STOT RE 1, H372
Aluminium oxide	-	CAS-No.: 1344-28-1	10 – 25	Not classified
dibenzoyl peroxide	-	CAS-No.: 94-36-0	5 – 10	Org. Perox. B, H241 Eye Irrit. 2A, H319 Skin Sens. 1, H317
glycerol	1,2,3-propane triol / 1,2,3-propanetriol / 1,2,3-trihydroxypropane / 90 technical glycerine / citifluor AF 2 / E422 / glycerene / glycerin / glycerin mist / glycerin USP / glycerin, anhydrous / glycerin, synthetic / glycerine / glyceritol / glycerol / glycol alcohol / glyrol / grocolene / IFP (=glycerol) / incorporation factor (=glycerol) / MOON (=glycerol) / osmoglyn / star (=glycerol) / superol (=1,2,3-propanetriol) / synthetic glycerin / trihydroxypropane	CAS-No.: 56-81-5	1 – 1.5	Not classified

HIT-HY 100, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	Wash contaminated clothing before reuse. Wash with plenty of water/.... If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	Rinse mouth. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.
First-aid measures general	Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact	May cause an allergic skin reaction.
Symptoms/effects after eye contact	May cause severe irritation.
Potential adverse human health effects and symptoms	No additional information available.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	Treat symptomatically.
-----------------------------------	------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	Water spray. Carbon dioxide. Dry powder. Foam. Sand.
Unsuitable extinguishing media	Do not use a heavy water stream.

5.2. Specific hazards arising from the hazardous product

Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide. Carbon monoxide.
--	--

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Spilled material may present a slipping hazard.
------------------	---

6.2. Methods and materials for containment and cleaning up

For containment	Collect spillage.
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. Store away from other materials.
Other information	Dispose of materials or solid residues at an authorized site.



HIT-HY 100, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

For further information refer to section 8: "Exposure controls/personal protection", For further information refer to section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.

Hygiene measures

Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

Keep cool. Protect from sunlight.

Incompatible products

Strong bases. Strong acids.

Incompatible materials

Sources of ignition. Direct sunlight.

Heat and ignition sources

Keep away from heat and direct sunlight.

Storage temperature

5 – 25 °C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

HIT-HY 100, B

Canada (Alberta) - Occupational Exposure Limits

Local name

Benzoyl peroxide (Dibenzoyl peroxide)

OEL TWA

5 mg/m³

Notations and remarks

Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required.

Regulatory reference

Alberta Regulation 191/2021

Canada (British Columbia) - Occupational Exposure Limits

Local name

Benzoyl peroxide

OEL TWA

5 mg/m³

Regulatory reference

OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)

Canada (Manitoba) - Occupational Exposure Limits

Local name

Benzoyl peroxide

OEL TWA

5 mg/m³

Notations and remarks

TLV® Basis: URT & skin irr. Notations: A4 (Not classifiable as a Human Carcinogen)

Regulatory reference

ACGIH 2024

Canada (New Brunswick) - Occupational Exposure Limits

Local name

Benzoyl peroxide

OEL TWA

5 mg/m³



HIT-HY 100, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

HIT-HY 100, B	
Notations and remarks	URT & skin irr
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Benzoyl peroxide
OEL TWA	5 mg/m ³
Notations and remarks	TLV® Basis: URT & skin irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Benzoyl peroxide
OEL TWA	5 mg/m ³
Notations and remarks	TLV® Basis: URT & skin irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Benzoyl peroxide
OEL TWA	5 mg/m ³
OEL STEL	10 mg/m ³
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Quartz (SiO ₂) (14808-60-7)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Silica-Crystalline: Quartz
OEL TWA	0.025 mg/m ³ Respirable particulate
Notations and remarks	Carcinogenicity A2
Regulatory reference	Alberta Regulation 191/2021
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Silica, Crystalline - alpha quartz
OEL TWA	0.025 mg/m ³ Respirable
Notations and remarks	ACGIH Carcinogenicity category A2; IARC group 1 carcinogen
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Silica, crystalline, quartz
OEL TWA	0.025 mg/m ³ (R - Respirable particulate matter)
Notations and remarks	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)



HIT-HY 100, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

Quartz (SiO ₂) (14808-60-7)	
Regulatory reference	ACGIH 2025
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Silica, crystalline, quartz
OEL TWA	0.025 mg/m ³ (R - Respirable particulate matter)
Notations and remarks	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Regulatory reference	ACGIH 2025
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Silica, crystalline, quartz
OEL TWA	0.025 mg/m ³ (R - Respirable particulate matter)
Notations and remarks	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Regulatory reference	ACGIH 2025
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Silica - Crystalline: Quartz
OEL TWA	0.05 mg/m ³ (respirable fraction)
Notations and remarks	Designated substance
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Aluminium oxide (1344-28-1)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Aluminum oxide (Alumina)
OEL TWA	10 mg/m ³
Regulatory reference	Alberta Regulation 191/2021
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Aluminum oxide
OEL TWA	10 mg/m ³
OEL STEL	20 mg/m ³
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
dibenzoyl peroxide (94-36-0)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Benzoyl peroxide (Dibenzoyl peroxide)
OEL TWA	5 mg/m ³
Notations and remarks	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required.



HIT-HY 100, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

dibenzoyl peroxide (94-36-0)	
Regulatory reference	Alberta Regulation 191/2021
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Benzoyl peroxide
OEL TWA	5 mg/m ³
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Benzoyl peroxide
OEL TWA	5 mg/m ³
Notations and remarks	TLV® Basis: URT & skin irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH
Canada (New Brunswick) - Occupational Exposure Limits	
Local name	Benzoyl peroxide
OEL TWA	5 mg/m ³
Notations and remarks	URT & skin irr
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Benzoyl peroxide
OEL TWA	5 mg/m ³
Notations and remarks	TLV® Basis: URT & skin irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Benzoyl peroxide
OEL TWA	5 mg/m ³
Notations and remarks	TLV® Basis: URT & skin irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Benzoyl peroxide
OEL TWA	5 mg/m ³
OEL STEL	10 mg/m ³
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)

HIT-HY 100, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

Eye protection:		
Wear security glasses which protect from splashes		
Type	Field of application	Characteristics
Safety glasses	Droplet	clear

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	white
Odour	characteristic
Odour threshold	Not determined
pH	≈ 6
Relative evaporation rate (butylacetate=1)	No data available
Relative evaporation rate (ether=1)	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	No data available
Flash point	No data available
Auto-ignition temperature	Not self-igniting
Decomposition temperature	≈ 65 °C SADT
Flammability (solid, gas)	Flammable
Vapour pressure	No data available
Relative vapour density at 20°C	No data available
Relative density	No data available
Density	2 g/cm ³ DIN 66137-2
Solubility	Water: Not miscible
Partition coefficient n-octanol/water (Log Pow)	No data available
Viscosity, kinematic	35000 mm ² /s
Viscosity, dynamic	70 Pa·s HN-0333
Explosive properties	Product is not explosive.
Explosive limits	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

Reactivity	No additional information available
Chemical stability	Stable under normal conditions.



HIT-HY 100, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

Possibility of hazardous reactions	No additional information available.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures.
Incompatible materials	Strong acids. Strong bases.
Hazardous decomposition products	fume. Carbon monoxide. Carbon dioxide. Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

Aluminium oxide (1344-28-1)	
LD50 oral rat	> 15900 mg/kg
LC50 Inhalation - Rat	7.6 mg/l
LC50 Inhalation - Rat (Dust/Mist)	> 2.3 mg/l/4h (OECD 403 method)

glycerol (56-81-5)	
LD50 oral rat	27200 mg/kg (OECD 401: Acute Oral Toxicity, Rat, Female, Experimental value, Oral, 10 day(s))
LD50 dermal	56750 mg/kg (4 day(s), Guinea pig, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 5.85 mg/l (Equivalent or similar to OECD 412, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))

Skin corrosion/irritation	Not classified pH: ≈ 6
Serious eye damage/irritation	Not classified pH: ≈ 6
Respiratory or skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified

Quartz (SiO ₂) (14808-60-7)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	Known Human Carcinogens

dibenzoyl peroxide (94-36-0)	
IARC group	3 - Not classifiable
Reproductive toxicity	Not classified
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified

Quartz (SiO ₂) (14808-60-7)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not classified

HIT-HY 100, B	
Viscosity, kinematic	35000 mm ² /s



HIT-HY 100, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

Potential adverse human health effects and symptoms	No additional information available.
Symptoms/effects after skin contact	May cause an allergic skin reaction.
Symptoms/effects after eye contact	May cause severe irritation.

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	Not classified
Hazardous to the aquatic environment, long-term (chronic)	Not classified

dibenzoyl peroxide (94-36-0)	
LC50 - Fish [2]	0.0602 mg/l (96h; Oncorhynchus mykiss; ECHA)
EC50 - Crustacea [1]	0.11 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 algae	0.0711 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
NOEC chronic fish	0.001 mg/l
NOEC (acute)	0.0316 mg/l (96h; Oncorhynchus mykiss; ECHA)
glycerol (56-81-5)	
LC50 - Fish [1]	54000 mg/l (96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	> 10000 mg/l (24 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)

12.2. Persistence and degradability

HIT-HY 100, B	
Persistence and degradability	Not established.
Quartz (SiO ₂) (14808-60-7)	
Not rapidly degradable	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
Aluminium oxide (1344-28-1)	
Not rapidly degradable	
Persistence and degradability	Not applicable.
dibenzoyl peroxide (94-36-0)	
Persistence and degradability	Readily biodegradable in water. Not established. May cause long-term adverse effects in the environment.



HIT-HY 100, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

glycerol (56-81-5)	
Not rapidly degradable	
Persistence and degradability	Readily biodegradable in water.

12.3. Bioaccumulative potential

HIT-HY 100, B	
Bioaccumulative potential	Not established.
Quartz (SiO ₂) (14808-60-7)	
Bioaccumulative potential	No bioaccumulation data available.
Aluminium oxide (1344-28-1)	
Bioaccumulative potential	Not applicable.
dibenzoyl peroxide (94-36-0)	
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).
Partition coefficient n-octanol/water (Log Pow)	3.71
glycerol (56-81-5)	
Bioaccumulative potential	Not bioaccumulative.
Partition coefficient n-octanol/water (Log Pow)	-1.75 (Experimental value, Equivalent or similar to OECD 107, 25 °C)

12.4. Mobility in soil

Quartz (SiO ₂) (14808-60-7)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for mobility in soil.
dibenzoyl peroxide (94-36-0)	
Surface tension	No data available (test not performed)
Ecology - soil	Low potential for mobility in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
glycerol (56-81-5)	
Surface tension	63 mN/m (20 °C, 1000 g/l)
Ecology - soil	Highly mobile in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

12.5. Other adverse effects

Ozone	Not classified
Other information	Avoid release to the environment.

HIT-HY 100, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation	Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.
Ecological waste information	Avoid release to the environment.

SECTION 14: Transport information

In accordance with TDG / DOT / IMDG / IATA

TDG	DOT	IMDG	IATA
		Special provision(s) applied : 969	Special provision(s) applied : A197
14.1. UN number			
UN3077	3077	3077	3077
14.2. Proper Shipping Name			
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	Environmentally hazardous substances, solid, n.o.s.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	Environmentally hazardous substance, solid, n.o.s.
14.3. Transport hazard class(es)			
9	9	9	9
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes
not restricted according ADR Special Provision SP375, IATA-DGR Special Provision A197 and IMDG-Code 2.10.2.7			

14.6. Special precautions for user

TDG UN-No. (TDG)	UN3077
---------------------	--------



HIT-HY 100, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

TDG Special Provisions

16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the danger or dangers posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3).

(2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name:

- (a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S.;
- (b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S.;
- (c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S.;
- (d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S. or
- (e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S.

(3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment:

- (a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or
- (b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS, 99 - (1) Mixtures of solids that are not dangerous goods and liquids or solids that are UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. or UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., may be offered for transport, handled or transported as UN3077 if there is no visible liquid when the dangerous goods are loaded into a means of containment and during transport.

(2) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no release of the dangerous goods that could endanger public safety.

Explosive Limit and Limited Quantity Index
Excepted quantities (TDG)
Emergency Response Guide (ERG) Number

5 kg
E1
171

DOT
UN-No. (DOT)

UN3077



HIT-HY 100, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

DOT Special Provisions (49 CFR 172.102)

8 - A hazardous substance that is not a hazardous waste may be shipped under the shipping description "Other regulated substances, liquid or solid, n.o.s.", as appropriate. In addition, for solid materials, special provision B54 applies.

146 - This description may be used for a material that poses a hazard to the environment but does not meet the definition for a hazardous waste or a hazardous substance, as defined in 171.8 of this subchapter, or any hazard class as defined in Part 173 of this subchapter, if it is designated as environmentally hazardous by the Competent Authority of the country of origin, transit or destination.

335 - Mixtures of solids that are not subject to this subchapter and environmentally hazardous liquids or solids may be classified as "Environmentally hazardous substances, solid, n.o.s." UN3077 and may be transported under this entry, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each transport unit must be leakproof when used as bulk packaging.

384 - For transportation by motor vehicle, substances meeting the conditions for high viscosity flammable liquids as prescribed in §173.121(b)(1)(i), (b)(1)(ii), and (b)(1)(iv) of this subchapter, may be reassigned to Packing Group III under the following conditions:

A112 - Notwithstanding the quantity limits shown in Column (9A) and (9B) for this entry, the following IBCs are authorized for transportation aboard passenger and cargo-only aircraft. Each IBC may not exceed a maximum net quantity of 1,000 kg:

a. Metal: 11A, 11B, 11N, 21A, 21B and 21N

b. Rigid plastics: 11H1, 11H2, 21H1 and 21H2

c. Composite with plastic inner receptacle: 11HZ1, 11HZ2, 21HZ1 and 21HZ2

d. Fiberboard: 11G

e. Wooden: 11C, 11D and 11F (with inner liners)

f. Flexible: 13H2, 13H3, 13H4, 13H5, 13L2, 13L3, 13L4, 13M1 and 13M2 (flexible IBCs must be sift-proof and water resistant or must be fitted with a sift-proof and water resistant liner).

B54 - Open-top, sift-proof rail cars are also authorized.

B120 - The use of flexible bulk containers conforming to the requirements in subpart R and subpart S of part 178 of this subchapter is permitted.

IB8 - Authorized IBCs: Metal (11A, 11B, 11N, 21A, 21B, 21N, 31A, 31B and 31N); Rigid plastics (11H1, 11H2, 21H1, 21H2, 31H1 and 31H2); Composite (11HZ1, 11HZ2, 21HZ1, 21HZ2, 31HZ1 and 31HZ2); Fiberboard (11G); Wooden (11C, 11D and 11F); Flexible (13H1, 13H2, 13H3, 13H4, 13H5, 13L1, 13L2, 13L3, 13L4, 13M1 or 13M2).

IP3 - Flexible IBCs must be sift-proof and water-resistant or must be fitted with a sift-proof and water-resistant liner.

N20 - A 5M1 multi-wall paper bag is authorized if transported in a closed transport vehicle.

N91 - The use of a non specification sift-proof, non-bulk, metal can with or without lid, or a non specification sift-proof, non-bulk fiber drum, with or without lid is authorized when transporting coal tar pitch compounds by motor vehicle or rail freight. The fiber drum must be fabricated with a three ply wall, as a minimum. The coal tar pitch compound must be in a solid mass during transportation.

T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2)

TP33 - The portable tank instruction assigned for this substance applies for granular and powdered solids and for solids which are filled and discharged at temperatures above their melting point which are cooled and transported as a solid mass. Solid substances transported or offered for transport above their melting point are authorized for transportation in portable tanks conforming to the provisions of portable tank instruction T4 for solid substances of packing group III or T7 for solid substances of packing group II, unless a tank with more stringent requirements for minimum shell thickness, maximum allowable working pressure, pressure-relief devices or bottom outlets are assigned in which case the more stringent tank instruction and special provisions shall apply. Filling limits must be in accordance with portable tank special provision TP3. Solids meeting the definition of an elevated temperature material must be transported in accordance with the applicable requirements of this subchapter.

DOT Packaging Exceptions (49 CFR 173.xxx)

155



HIT-HY 100, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR), as amended by SOR/2022-272

DOT Packaging Non Bulk (49 CFR 173.xxx)	213
DOT Packaging Bulk (49 CFR 173.xxx)	240
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	No Limit
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	No Limit
DOT Vessel Stowage Location	A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

IMDG

Special provisions (IMDG)	274, 335, 375, 966, 967, 969
Limited quantities (IMDG)	5 kg
Packing instructions (IMDG)	LP02, P002
EmS-No. (Fire)	F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage)	S-F - SPILLAGE SCHEDULE Foxtrot - WATER-SOLUBLE MARINE POLLUTANTS
Stowage category (IMDG)	A
Stowage and handling (IMDG)	SW23

IATA

PCA packing instructions (IATA)	956
PCA max net quantity (IATA)	400kg
CAO packing instructions (IATA)	956
Special provisions (IATA)	A97, A158, A179, A197, A215

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

HIT-HY 100, B	
Canada DSL & NDSL Flags	All components of this product are listed, or excluded from listing, on the Canadian Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

Quartz (SiO₂) (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List)

Aluminium oxide (1344-28-1)

Listed on the Canadian DSL (Domestic Substances List)

dibenzoyl peroxide (94-36-0)

Listed on the Canadian DSL (Domestic Substances List)

glycerol (56-81-5)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: Other information

Issue date 12-05-2025



HIT-HY 100, B

Safety Data Sheet

according to SOR/2015-17, Hazardous Products Regulations (HPR) , as amended by SOR/2022-272

Revision date 12-05-2025
Supersedes 07-28-2025

Indication of changes			
Section	Changed item	Change	Comments
14	Transport information	Modified	

Other information None.

Full text of hazard classes and H-statements:	
H241	Heating may cause a fire or explosion
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.

SDS_CA_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.