



























		Size		Hole Cleaning Option ¹⁴			Head Type				Base Material				Corrosion Resistance			Features		Approvals		
		Minimum Size Diameter	Maximum Size Diameter	Standard Cleaning (blow, brush, blow)	Self Cleaning with TE-CD/YD Hollow Drill Bit ¹¹	Non Cleaning with specialty HIT-Z Rod	Stud (Externally Threaded)	Flush or Internally Threaded	Rebar	Hex Bolt	Round/Mushroom	Concrete	Lightweight Concrete	Grout-filled Block	Hollow Block/Brick ¹²	Hot-dip Galvanized Steel	304 Stainless Steel	316 Stainless Steel	Seismic	Cracked Concrete (per ICC-ES) ¹³		
Adhesive	HIT HY 200-A Injectable Mortar		3/8"	1-1/4"	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	3a, 4, 6, 7, 8, 9
	HIT HY 200-R Injectable Mortar		3/8"	1-1/4"	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	3a, 4, 6, 7, 8, 9
	HIT-HY 100 Injectable Mortar		3/8"	1-1/4"	■			■	■	■		■	■	■	■	■	■	■	■	A-B	■	3a, 6, 7, 8, 9
	HIT-HY 10 PLUS Injectable Mortar		3/8"	3/4"	■			■	■	■		■	□	■	■	■	■	■	■			7
	HIT-HY 70 Injectable Mortar		1/4"	3/4"	■			■	■	■				■	■	■	■	■	■			3b, 3c, 3d, 4, 7, 8, 9
	HIT-RE 500-SD Injectable Mortar		3/8"	1-1/4"	■			■	■	■		■	■	■	■	■	■	■	■	■	■	3a, 4, 6, 7, 8, 9
	HIT-RE 500 Injectable Mortar		3/8"	>1-1/4"	■			■	■	■		■	□	■	■	■	■	■	■			6, 7
	HIT-ICE Injectable Mortar		3/8"	1-1/4"	■			■	■	■		■	■	■	■	■	■	■	■			7
	HVU Adhesive Anchor Capsule System		3/8"	1-1/4"	■			■	■	■		■	□	□	■	■	■	■	■			7
	HIT-Z Anchor rod		3/8"	3/4"	■	■	■	■				■ ¹⁶	■ ¹⁶						■ ¹⁶	■ ¹⁶		7
	HAS Anchor rod		1/4"	1-1/4"	■	■		■				■ ¹⁶	■ ¹⁶	■ ¹⁶	■ ¹⁶	■ ^{7/8"}	■	■	■ ¹⁶	■ ¹⁶		7
	HIT-V Anchor rod		3/8"	1"	■	■		■				■ ¹⁶	■ ¹⁶	■ ¹⁶	■ ¹⁶				■ ¹⁶	■ ¹⁶		7
Mechanical	HDA Undercut Anchor		M10	M20			■				■	□			■ ¹⁵	■	■	■	■		3a, 4, 7, 8, 9, 10	
	HSL-3 Heavy-duty Expansion Anchor		M8	M24			■		■		■	□						■	■		3a, 4, 7, 8, 9, 10	
	KWIK Bolt-TZ Expansion Anchor		3/8"	3/4"			■					■	■			■	■	■	■			1, 2, 3a, 4, 7, 8, 9, 10
	KWIK Bolt 3 Expansion Anchor		1/4"	1"			■	■				■	■	■	■	■	■	■	■	A-B		1, 2, 3a, 3b, 4, 5, 7, 8, 9, 10
	KWIK Bolt-V Expansion Anchor		1/4"	3/4"			■					■	■	■		■	■	■				2, 7
	KWIK HUS-EZ Screw Anchor		1/4"	3/4"						■		■	■	■					■	■		3a, 3b, 4, 7, 8, 9, 10
	KWIK HUS Screw Anchor		3/8"	3/4"						■		■	■	□								7
	HCA Reusable Coil Anchor		1/4"	3/4"						■		■	□									-
	HLC Sleeve Anchor		1/4"	3/4"			■					■	□	■	■		■					7
	KWIK HUS-EZ-I Screw Anchor		1/4"	3/8"								■	■						■	■		1, 3a, 4, 7, 8, 9, 10
	HDI / HDI-L / HDI+ Drop-in Anchor HDI+ Stop Drill Bit with Setting Tool available		1/4"	3/4"								■	■				■	303 SS				1, 2, 7
	HDI-P Flush Anchor		3/8"	3/8"								■	□									7
	HCI Cast-in Anchor Color Coded: ●●●●●		1/4"	3/4"								■	■									1, 2, 7
	KWIK-CON II Concrete and Masonry Screw		3/16"	1/4"								■	□	□	■			■	410 SS			5, 7

11 Hollow Drill Bit must be used in conjunction with Hilti vacuum cleaner. Consult ordering information for application range.
 12 Requires screen tube.
 13 For anchor design purposes, concrete is assumed to be cracked if cracks could form in the concrete at or near the anchor location over the service life of the anchor.
 14 Consult "instructions for use" provided in product packaging or contact your Hilti representative.
 15 Sheradized, average 53 µm zinc. Has equivalent corrosion resistance to hot dip galvanized steel.
 16 To confirm suitability please consult technical data and "instructions for use".

* Approval pending
 ■ Suitable
 □ May be Suitable — application specific

Additional sizes may be available through special order.
 Contact Hilti or refer to the Hilti Product Technical Guide for additional information.